

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## ASTM B409-87 STANDARD SPECIFICATION FOR NICKEL-IRON-CHROMIUM ALLOY PLATE, SHEET, AND STRIP

[View on Information Provider website](#)

Abbreviation  
ASTM B409-87  
Valid from  
27/02/1987

---

Information provider  
IHS Markit  
Author  
American Society of Testing and Materials  
Information type  
ASTM Standard  
Format  
PDF, Hard copy

---

Cited By  
[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This specification covers UNS N08120, UNS N08890, UNS N08800, UNS N08810, and UNS N08811 in the form of rolled plate, sheet, and strip.

Alloy UNS N08800 is normally employed in service temperatures up to and including 1100°F (593°C).

Alloys UNS N08120, UNS N08810, UNS N08811, and UNS N08890 are normally employed in service temperatures above 1100°F (593°C) where resistance to creep and rupture is required, and they are annealed to develop controlled grain size for optimum properties in this temperature range.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## ASTM B409-87 STANDARD SPECIFICATION FOR NICKEL-IRON-CHROMIUM

# ALLOY PLATE, SHEET, AND STRIP

This document is CITED BY:

- [ANSI/ASME B16.5: 1988](#)

ASTM B409-87 is cited by ANSI/ASME B16.5: 1988 Pipe flanges and flanged fittings, steel-nickel alloy and other special alloys

Back

## ASTM B409-87 STANDARD SPECIFICATION FOR NICKEL-IRON-CHROMIUM ALLOY PLATE, SHEET, AND STRIP

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This specification covers UNS N08120, UNS N08890, UNS N08800, UNS N08810, and UNS N08811 in the form of rolled plate, sheet, and strip.

Alloy UNS N08800 is normally employed in service temperatures up to and including 1100° F (593° C).

Alloys UNS N08120, UNS N08810, UNS N08811, and UNS N08890 are normally employed in service temperatures above 1100° F (593° C) where resistance to creep and rupture is required, and they are annealed to develop controlled grain size for optimum properties in this temperature range.

[View on Information Provider website](#)

### [ASTM B409-87 STANDARD SPECIFICATION FOR NICKEL-IRON-CHROMIUM ALLOY PLATE, SHEET, AND STRIP](#)

### Description

This specification covers UNS N08120, UNS N08890, UNS N08800, UNS N08810, and UNS N08811 in the form of rolled plate, sheet, and strip.

Alloy UNS N08800 is normally employed in service temperatures up to and including 1100° F (593° C).

Alloys UNS N08120, UNS N08810, UNS N08811, and UNS N08890 are normally employed in service temperatures above 1100° F (593° C) where resistance to creep and rupture is required, and they are annealed to develop controlled grain size for optimum properties in this temperature range.

[View on Information Provider website](#)

This resource does not cite any other resources.

## ASTM B409-87 STANDARD SPECIFICATION FOR NICKEL-IRON-CHROMIUM ALLOY PLATE, SHEET, AND STRIP

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)