

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ASTM B572-87 STANDARD SPECIFICATION FOR UNS N06002 AND UNS R30556 ROD

[View on Information Provider website](#)

Abbreviation
ASTM B572-87
Valid from
27/02/1987

Information provider
IHS Markit
Author
American Society of Testing and Materials
Information type
ASTM Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This specification covers alloys UNS N06002, UNS N06230, UNS N12160, and UNS R30556 in the form of rod for heat resisting and general-corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) exclusive in diameter, hot or cold finished, solution-annealed, and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) inclusive in diameter, hot or cold finished, solution annealed, ground, or turned.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ASTM B572-87 STANDARD SPECIFICATION FOR UNS N06002 AND UNS R30556

ROD

This document is CITED BY:

- [ANSI/ASME B16.5: 1988](#)

ASTM B572-87 is cited by ANSI/ASME B16.5: 1988 Pipe flanges and flanged fittings, steel-nickel alloy and other special alloys

Back

ASTM B572-87 STANDARD SPECIFICATION FOR UNS N06002 AND UNS R30556 ROD

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This specification covers alloys UNS N06002, UNS N06230, UNS N12160, and UNS R30556 in the form of rod for heat resisting and general-corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) exclusive in diameter, hot or cold finished, solution-annealed, and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) inclusive in diameter, hot or cold finished, solution annealed, ground, or turned.

[View on Information Provider website](#)

[ASTM B572-87 STANDARD SPECIFICATION FOR UNS N06002 AND UNS R30556 ROD](#)

Description

This specification covers alloys UNS N06002, UNS N06230, UNS N12160, and UNS R30556 in the form of rod for heat resisting and general-corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) exclusive in diameter, hot or cold finished, solution-annealed, and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) inclusive in diameter, hot or cold finished, solution annealed, ground, or turned.

[View on Information Provider website](#)

This resource does not cite any other resources.

ASTM B572-87 STANDARD SPECIFICATION FOR UNS N06002 AND UNS R30556 ROD

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)