

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ASTM B581-86 STANDARD SPECIFICATION FOR NICKEL-CHROMIUM- IRON- MOLYBDENUM-COPPER ALLOY ROD

[View on Information Provider website](#)

Abbreviation

ASTM B581-86

Valid from

28/02/1986

Information provider

IHS Markit

Author

American Society of Testing and Materials

Information type

ASTM Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This specification covers rod of Ni-Cr-Fe-Mo-Cu alloys (UNS N06007, N06975, N06985, N06030, N08031, and N08034), for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot- or cold-finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot- or cold-finished, solution annealed, ground or turned.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ASTM B581-86 STANDARD SPECIFICATION FOR NICKEL-CHROMIUM- IRON-

MOLYBDENUM-COPPER ALLOY ROD

This document is CITED BY:

- [ANSI/ASME B16.5: 1988](#)

ASTM B581-86 is cited by ANSI/ASME B16.5: 1988 Pipe flanges and flanged fittings, steel-nickel alloy and other special alloys

Back

ASTM B581-86 STANDARD SPECIFICATION FOR NICKEL-CHROMIUM- IRON- MOLYBDENUM-COPPER ALLOY ROD

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This specification covers rod of Ni-Cr-Fe-Mo-Cu alloys (UNS N06007, N06975, N06985, N06030, N08031, and N08034), for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot- or cold-finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot- or cold-finished, solution annealed, ground or turned.

[View on Information Provider website](#)

[ASTM B581-86 STANDARD SPECIFICATION FOR NICKEL-CHROMIUM- IRON-MOLYBDENUM-COPPER ALLOY ROD](#)

Description

This specification covers rod of Ni-Cr-Fe-Mo-Cu alloys (UNS N06007, N06975, N06985, N06030, N08031, and N08034), for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot- or cold-finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot- or cold-finished, solution annealed, ground or turned.

[View on Information Provider website](#)

This resource does not cite any other resources.

ASTM B581-86 STANDARD SPECIFICATION FOR NICKEL-CHROMIUM- IRON- MOLYBDENUM-COPPER ALLOY ROD

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)