

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## ASTM B621-83A STANDARD SPECIFICATION FOR NICKEL-IRON- CHROMIUM- MOLYBDENUM ALLOY (UNS N08320) ROD

[View on Information Provider website](#)

### Abbreviation

ASTM B621-83A

### Valid from

29/07/1983

---

### Information provider

IHS Markit

### Author

American Society of Testing and Materials

### Information type

ASTM Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This specification covers nickel-iron chromium-molybdenum alloy (UNS N08320) rod for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## ASTM B621-83A STANDARD SPECIFICATION FOR NICKEL-IRON- CHROMIUM- MOLYBDENUM ALLOY (UNS N08320) ROD

This document is CITED BY:

- [ANSI/ASME B16.5: 1988](#)

ASTM B621-83A is cited by ANSI/ASME B16.5: 1988 Pipe flanges and flanged fittings, steel-nickel alloy and other special alloys

Back

## ASTM B621-83A STANDARD SPECIFICATION FOR NICKEL-IRON- CHROMIUM-MOLYBDENUM ALLOY (UNS N08320) ROD

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This specification covers nickel-iron chromium-molybdenum alloy (UNS N08320) rod for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

[View on Information Provider website](#)

### [ASTM B621-83A STANDARD SPECIFICATION FOR NICKEL-IRON- CHROMIUM-MOLYBDENUM ALLOY \(UNS N08320\) ROD](#)

### Description

This specification covers nickel-iron chromium-molybdenum alloy (UNS N08320) rod for use in general corrosive service.

The following products are covered under this specification:

- Rods 5/16 to 3/4 in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods 3/4 to 3 1/2 in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

[View on Information Provider website](#)

This resource does not cite any other resources.

## ASTM B621-83A STANDARD SPECIFICATION FOR NICKEL-IRON- CHROMIUM-MOLYBDENUM ALLOY (UNS N08320) ROD

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)