

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

ASTM C739 - 00e1 Standard Specification for Cellulosic Fiber (Wood-Base) Loose-Fill Thermal Insulation

[View on Information Provider website](#)

Abbreviation

ASTM C739 - 00e1

Valid from

10/05/2000

Information provider

American Society of Testing and Materials

Author

American Society of Testing and Materials

Information type

ASTM Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This specification covers the composition and physical requirements of chemically treated, recycled cellulosic fiber (wood-base) loose-fill type thermal insulation for use in attics or enclosed spaces in housing, and other framed buildings within the ambient temperature range from -45.6 to 82.2°C (-50 to 180°F) by pneumatic or pouring application. While products that comply with this specification may be used in various constructions, they are adaptable primarily, but not exclusively, to wood joist, rafters, and stud construction.

The values stated in SI units are to be regarded as the standard. The values in parentheses are provided for information only.

This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

Scope

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ASTM C739 - 00e1 Standard Specification for Cellulosic Fiber (Wood-Base) Loose-Fill Thermal Insulation

This document is CITED BY:

- [AS/NZS 4859.1:2002](#)

ASTM C739 - 00e1 is cited by AS/NZS 4859.1:2002 Materials for the thermal insulation of buildings - General criteria and technical provisions

[Back](#)

ASTM C739 - 00e1 Standard Specification for Cellulosic Fiber (Wood-Base) Loose-Fill Thermal Insulation

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This specification covers the composition and physical requirements of chemically treated, recycled cellulosic fiber (wood-base) loose-fill type thermal insulation for use in attics or enclosed spaces in housing, and other framed buildings within the ambient temperature range from -45.6 to 82.2°C (-50 to 180°F) by pneumatic or pouring application. While products that comply with this specification may be used in various constructions, they are adaptable primarily, but not exclusively, to wood joist, rafters, and stud construction.

The values stated in SI units are to be regarded as the standard. The values in parentheses are provided for information only.

This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

[View on Information Provider website](#)

[ASTM C739 - 00e1 Standard Specification for Cellulosic Fiber \(Wood-Base\) Loose-Fill Thermal Insulation](#)

Description

This specification covers the composition and physical requirements of chemically treated, recycled cellulosic fiber (wood-base) loose-fill type thermal insulation for use in attics or enclosed spaces in housing, and other framed buildings within the ambient temperature range from -45.6 to 82.2°C (-50 to 180°F) by pneumatic or pouring application. While products that comply with this specification may be used in various constructions, they are adaptable primarily, but not exclusively, to wood joist, rafters, and stud construction.

The values stated in SI units are to be regarded as the standard. The values in parentheses are provided for information only.

This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

[View on Information Provider website](#)

This resource does not cite any other resources.

ASTM C739 - 00e1 Standard Specification for Cellulosic Fiber (Wood-Base) Loose-Fill Thermal Insulation

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)