

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## ASTM D2846 / D2846M - 09be1 Standard Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Hot- and Cold-Water Distribution Systems

[View on Information Provider website](#)

### Abbreviation

ASTM D2846 / D2846M - 09be1

### Valid from

01/08/2009

---

### Information provider

American Society of Testing and Materials

### Author

American Society of Testing and Materials

### Information type

ASTM Standard

### Format

PDF

---

### Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

---

### Description

This specification covers requirements, test methods, and methods of marking for chlorinated poly(vinyl chloride) plastic hot- and cold-water distribution system components made in one standard dimension ratio and intended for water service up to and including 180° F (82° C).

These components comprise pipe and tubing, socket-type fittings, street fittings, plastic-to-metal transition fittings, solvent cements, and adhesives.

### Scope

Requirements and methods of test are included for materials, workmanship, dimensions and tolerances, hydrostatic sustained pressure strength, and thermocycling resistance. The components covered by this specification are intended for use in residential and commercial, hot and cold, potable water distribution systems.

The products covered by this specification are intended for use with the distribution of pressurized liquids only, which are chemically compatible with the piping materials. Due to inherent hazards associated with testing components and systems with compressed air or other compressed gases some manufacturers do not allow pneumatic testing of their products. Consult with specific product/component manufacturers for their specific testing procedures prior to pneumatic testing.

**Note 1**—Pressurized (compressed) air or other compressed gases contain large amounts of stored energy which present serious safety hazards should a system fail for any reason.

The text of this specification references notes, footnotes, and appendixes which provide explanatory material. These notes and footnotes (excluding those in tables and figures) shall not be considered as requirements of the specification.

The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

**Note 2**—Suggested hydrostatic design stresses and hydrostatic pressure ratings for pipe, tubing, and fittings are listed in Appendix X1. Design, assembly, and installation considerations are discussed in Appendix X2. An optional performance qualification and an in-plant quality control program are recommended in Appendix X3.

The following safety hazards caveat pertains only to the test method portion, Sections 9 and 10, of this specification: This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## **ASTM D2846 / D2846M - 09be1 Standard Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Hot- and Cold-Water Distribution Systems**

This document is CITED BY:

- [AS/NZS 3500.1:2015](#)

ASTM D2846 / D2846M - 09be1 is cited by AS/NZS 3500.1:2015 Plumbing and drainage - Part 1: Water services

- [AS/NZS 3500.4:2015](#)

ASTM D2846 / D2846M - 09be1 is cited by AS/NZS 3500.4:2015 Plumbing and drainage - Heated water services

## **ASTM D2846 / D2846M - 09be1 Standard Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Hot- and Cold-Water Distribution Systems**

Description

This specification covers requirements, test methods, and methods of marking for chlorinated poly(vinyl chloride) plastic hot- and cold-water distribution system components made in one standard dimension ratio and intended for water service up to and including 180°F (82°C).

These components comprise pipe and tubing, socket-type fittings, street fittings, plastic-to-metal transition fittings, solvent cements, and adhesives.

[View on Information Provider website](#)

[ASTM D2846 / D2846M - 09be1 Standard Specification for Chlorinated Poly\(Vinyl Chloride\) \(CPVC\) Plastic Hot- and Cold-Water Distribution Systems](#)

Description

This specification covers requirements, test methods, and methods of marking for chlorinated poly(vinyl chloride) plastic hot- and cold-water distribution system components made in one standard dimension ratio and intended for water service up to and including 180° F (82° C).

These components comprise pipe and tubing, socket-type fittings, street fittings, plastic-to-metal transition fittings, solvent cements, and adhesives.

[View on Information Provider website](#)

This resource does not cite any other resources.

## ASTM D2846 / D2846M - 09be1 Standard Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Hot- and Cold-Water Distribution Systems

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)