

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)  
[Citations](#)

## ASTM D4285-83 (R2012) Standard Test Method for Indicating Oil or Water in Compressed Air

[View on Information Provider website](#)

### Abbreviation

ASTM D4285-83

### Valid from

30/09/1983

---

### Information provider

IHS Markit

### Author

American Society of Testing and Materials

### Information type

ASTM Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This test method is used to determine the presence of oil or water in compressed air used for abrasive blast cleaning, air blast cleaning, and coating application operations.

The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

### Scope

This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. For specific hazard statements.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

**This resource is cited by:**

# ASTM D4285-83 (R2012) Standard Test Method for Indicating Oil or Water in Compressed Air

This document is CITED BY:

- [AS/NZS 5131:2016](#)

ASTM D4285-83 is cited by AS/NZS 5131:2016 Structural steelwork - Fabrication and erection

Back

# ASTM D4285-83 (R2012) Standard Test Method for Indicating Oil or Water in Compressed Air

Show what documents this resource is CITED BY

Show what documents this resource CITES

## Description

This test method is used to determine the presence of oil or water in compressed air used for abrasive blast cleaning, air blast cleaning, and coating application operations.

The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

[View on Information Provider website](#)

[ASTM D4285-83 \(R2012\) Standard Test Method for Indicating Oil or Water in Compressed Air](#)

## Description

This test method is used to determine the presence of oil or water in compressed air used for abrasive blast cleaning, air blast cleaning, and coating application operations.

The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

[View on Information Provider website](#)

This resource does not cite any other resources.

# ASTM D4285-83 (R2012) Standard Test Method for Indicating Oil or Water in Compressed Air

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)