

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ASTM F493-14 Standard Specification for Solvent Cements for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe and Fittings

[View on Information Provider website](#)

Abbreviation

ASTM F493-14

Valid from

14/01/2015

Information provider

American Society of Testing and Materials

Author

American Society of Testing and Materials

Information type

ASTM Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This specification covers requirements for solvent cements for chlorinated poly(vinyl chloride) (CPVC) plastic pipe, tubing, and socket-type fittings. Solvent cement shall be a CPVC resin-based solution, shall be free-flowing, shall show no gelation or stratification, and shall not contain lumps or any foreign matter. Other requirements include resin content, dissolution, viscosity, shelf stability, hydrostatic burst strength, and hydrostatic sustained pressure strength. Test procedures for solid contents, inert filler determination, viscosity, hydrostatic burst strength, and hydrostatic sustained pressure strength are included in this specification.

Scope

This specification provides requirements for chlorinated poly(vinyl chloride) (CPVC) solvent cements to be used in joining chlorinated poly(vinyl chloride) pipe, tubing, and socket-type fittings.

CPVC solvent cements are used with CPVC 41 chlorinated poly(vinyl chloride) pipe, tubing, and fittings, which meet Class 23447 as defined in Specification D1784.

A recommended procedure for joining CPVC pipe and fittings is given in Appendix X1.

The text of this specification references notes, footnotes, and appendixes which provide explanatory material. These notes and footnotes (excluding those in tables and figures) shall not be considered as requirements of the specification.

The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical

conversions to SI units that are provided for information only and are not considered standard.

The following safety hazards caveat pertains only to the test methods portion, Section 6, of this specification: This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ASTM F493-14 Standard Specification for Solvent Cements for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe and Fittings

This document is CITED BY:

- [AS/NZS 3500.1:2015](#)

ASTM F493-14 is cited by AS/NZS 3500.1:2015 Plumbing and drainage - Part 1: Water services

- [AS/NZS 3500.1:2018](#)

ASTM F493-14 is cited by AS/NZS 3500.1:2018 Plumbing and drainage Part 1: Water services

ASTM F493-14 Standard Specification for Solvent Cements for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe and Fittings

Description

This specification covers requirements for solvent cements for chlorinated poly(vinyl chloride) (CPVC) plastic pipe, tubing, and socket-type fittings. Solvent cement shall be a CPVC resin-based solution, shall be free-flowing, shall show no gelation or stratification, and shall not contain lumps or any foreign matter. Other requirements include resin content, dissolution, viscosity, shelf stability, hydrostatic burst strength, and hydrostatic sustained pressure strength. Test procedures for solid contents, inert filler determination, viscosity, hydrostatic burst strength, and hydrostatic sustained pressure strength are included in this specification.

[View on Information Provider website](#)

[ASTM F493-14 Standard Specification for Solvent Cements for Chlorinated Poly\(Vinyl Chloride\) \(CPVC\) Plastic Pipe and Fittings](#)

Description

This specification covers requirements for solvent cements for chlorinated poly(vinyl chloride) (CPVC) plastic pipe, tubing, and socket-type fittings. Solvent cement shall be a CPVC resin-based solution, shall be free-flowing, shall show no gelation or stratification, and shall not contain lumps or any foreign matter. Other requirements include resin content, dissolution, viscosity, shelf stability, hydrostatic burst strength, and hydrostatic sustained pressure strength. Test procedures for solid contents, inert filler determination, viscosity, hydrostatic burst strength, and hydrostatic sustained pressure strength are included in this specification.

[View on Information Provider website](#)

This resource does not cite any other resources.

ASTM F493-14 Standard Specification for Solvent Cements for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe and Fittings

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)