Skip to main content Skip to primary navigation	Skip to main content Skip to primary pavigation		
<ul> <li>Skip to main content Skip to primary navigation</li> <li>Menu</li> <li>Home Home</li> <li>About this portal</li> </ul>			
		Latest updates	
Print <u>Save</u> Email			
Resource detail Citations			
		AWWA C651-99 Standard for Disinfecting Water Mains	
			Distincting trater mane
View on Information Provider website {{ linkText }}			
view on information Provider website 11 mm			
Abbreviation			
Abbreviation AWWA C651-99			
Abbreviation AWWA C651-99 Valid from 01/01/2000			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider American Water Works Association			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider American Water Works Association Author			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider American Water Works Association Author American Water Works Association			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider American Water Works Association Author			
Abbreviation AWWA C651-99 Valid from 01/01/2000 Information provider American Water Works Association Author American Water Works Association Information type			

### Cited By

This resource is cited by 1 document (show Citations)

#### Description

This standard presents essential procedures for the disinfection of new and repaired potable water mains. All new water mains shall be disinfected before they are placed in service. All water mains taken out of service for inspection, repair, or other activities that might lead to contamination of water shall be disinfected before they are returned to service.

Topics covered include forms of chlorine disinfection, a description of the disinfection procedure, preventive and corrective measures during construction, methods of chlorination, final flushing, bacteriological testing, redisinfection, final connections to existing mains, disinfection procedures when cutting into or repairing existing mains, and special procedures for caulked tapping sleeves.

Appendices cover chlorine residual testing, chlorine dosages, and disposal of heavily chlorinated water. The major revision in this edition of ANSI/AWWA C651-99 includes the following: the format has been changed to AWWA standard style.

For assistance with locating previous versions, please contact the information provider.

View on Information Provider website {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# AWWA C651-99 Standard for Disinfecting Water Mains

This document is CITED BY:

<u>AS/NZS 3500.1:2003</u>

AWWA C651-99 is cited by AS/NZS 3500.1:2003 Plumbing and drainage - Water services

Back

# AWWA C651-99 Standard for Disinfecting Water Mains

Show what documents this resource is CITED BY Show

Show what documents this resource CITES

#### Description

This standard presents essential procedures for the disinfection of new and repaired potable water mains. All new water mains shall be disinfected before they are placed in service. All water mains taken out of service for inspection, repair, or other activities that might lead to contamination of water shall be disinfected before they are returned to service.

Topics covered include forms of chlorine disinfection, a description of the disinfection procedure, preventive and corrective measures during construction, methods of chlorination, final flushing, bacteriological testing, redisinfection, final connections to existing mains, disinfection procedures when cutting into or repairing existing mains, and special procedures for caulked tapping sleeves.

Appendices cover chlorine residual testing, chlorine dosages, and disposal of heavily chlorinated water. The major revision in this edition of ANSI/AWWA C651-99 includes the following: the format has been changed to AWWA standard style.

View on Information Provider website

### AWWA C651-99 Standard for Disinfecting Water Mains

### Description

This standard presents essential procedures for the disinfection of new and repaired potable water mains. All new water mains shall be disinfected before they are placed in service. All water mains taken out of service for inspection, repair, or other activities that might lead to contamination of water shall be disinfected before they are returned to service.

Topics covered include forms of chlorine disinfection, a description of the disinfection procedure, preventive and corrective measures during construction, methods of chlorination, final flushing, bacteriological testing, redisinfection, final connections to existing mains, disinfection procedures when cutting into or repairing existing mains, and special procedures for caulked tapping sleeves.

Appendices cover chlorine residual testing, chlorine dosages, and disposal of heavily chlorinated water. The major revision in this edition of ANSI/AWWA C651-99 includes the following: the format has been changed to AWWA standard style.

## View on Information Provider website

This resource does not cite any other resources.

## AWWA C651-99 Standard for Disinfecting Water Mains

This resource does not CITE any other resources.

Back Close

Table of Contents

Print <u>Save</u> Email

<u>Feedback</u>

- <u>Contact us</u>
- Privacy policy
- <u>Disclaimer</u>
  <u>Copyright</u>

Feedback