

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

The ASCC DEMILEC HEATLOK XT Spray Applied PU Foam

[View on Information Provider website](#) [Download this resource \(PDF, 450KB\)](#)

Abbreviation

BCS-152216-CMNZ

Valid from

30/01/2018

Information provider

Ministry of Business, Innovation and Employment

Author

BEAL Certification Service Limited

Information type

Product Certificate (CodeMark)

Format

PDF

Description

The DEMILEC HEATLOK XT Foam supplied by ASCC Limited, is a closed cell, medium density 2-part polyurethane foam with low thermal conductivity that will adhere to numerous substrates.

The DEMILEC HEATLOK XT Spray Foam is used as a spray-in-place insulation product to provide a durable air-tight barrier to heat and cold.

The product is usually site applied using special spray equipment, trained applicators and under strict quality control conditions.

The product is typically used for application into timber and or light gauge steel framing of walls, floors and in roofs to meet thermal performance design requirements.

Scope

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 450KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

The ASCC DEMILEC HEATLOK XT Spray Applied PU Foam

This document is not CITED BY any other resources:

[Back](#)

The ASCC DEMILEC HEATLOK XT Spray Applied PU Foam

[Show what documents this resource is CITED BY](#)

[Show what documents this resource CITES](#)

Description

The DEMILEC HEATLOK XT Foam supplied by ASCC Limited, is a closed cell, medium density 2-part polyurethane foam with low thermal conductivity that will adhere to numerous substrates.

The DEMILEC HEATLOK XT Spray Foam is used as a spray-in-place insulation product to provide a durable air-tight barrier to heat and cold.

The product is usually site applied using special spray equipment, trained applicators and under strict quality control conditions.

The product is typically used for application into timber and or light gauge steel framing of walls, floors and in roofs to meet thermal performance design requirements.

[View on Information Provider website](#) [Download this resource \(PDF, 450KB\)](#)

[The ASCC DEMILEC HEATLOK XT Spray Applied PU Foam](#)

Description

The DEMILEC HEATLOK XT Foam supplied by ASCC Limited, is a closed cell, medium density 2-part polyurethane foam with low thermal conductivity that will adhere to numerous substrates.

The DEMILEC HEATLOK XT Spray Foam is used as a spray-in-place insulation product to provide a durable air-tight barrier to heat and cold.

The product is usually site applied using special spray equipment, trained applicators and under strict quality control conditions.

The product is typically used for application into timber and or light gauge steel framing of walls, floors and in roofs to meet thermal performance design requirements.

[View on Information Provider website](#) [Download this resource \(PDF, 450KB\)](#)

This resource does not cite any other resources.

The ASCC DEMILEC HEATLOK XT Spray Applied PU Foam

This resource does not CITE any other resources.

[Back](#)

[Close](#)

Table of Contents

[Print](#) [Save](#) [Email](#)

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)