Skip to main content Skip to primary navigation
Menu
• Home Home
About this portal
Latest updates
Print Savo Email
Print Save Email
Resource detail Citations
<u>Citations</u>
BS 1211:1958 Specification for centrifugally cast (spun) iron pressure pipes for
water, gas and sewage
View on Information Provider website {{ linkText }}
Abbreviation
BS 1211:1958
Valid from
24/02/1958
Information provider
British Standards Institution
Author
British Standards Institution
Information type
British Standard
Format
PDF
Cited By
This resource is cited by 1 document (show Citations)
Description
This Observational in all values are self-self-on form
This Standard includes specification for -
Pipes with spigot and socket joints cast in either metal or sand moulds,
Class B, field test pressure 400 ft head of water;
Class C, 600 ft head of water;
Class D, 800 ft head of water.
Also standard lengths, internal diameters, hydraulic tests and tests for straightness.
Also standard lengths, miernal diameters, nydradno tests and tests for straightness.
For assistance with locating previous versions, please contact the information provider.
View on Information Provider website {{ linkText }}
For assistance with locating previous versions, please contact the information provider.
This resource is cited by:

BS 1211:1958 Specification for centrifugally cast (spun) iron pressure pipes for water, gas and sewage

NZS 4442:1988

BS 1211:1958 is cited by NZS 4442:1988 Welded steel pipes and fittings for water, sewage and medium pressure gas



## BS 1211:1958 Specification for centrifugally cast (spun) iron pressure pipes for water, gas and sewage

Show what documents this resource is CITED BY

Show what documents this resource CITES

#### Description

This Standard includes specification for -

- Pipes with spigot and socket joints cast in either metal or sand moulds,
- Class B, field test pressure 400 ft head of water;
- Class C, 600 ft head of water;
- · Class D, 800 ft head of water.

Also standard lengths, internal diameters, hydraulic tests and tests for straightness.

View on Information Provider website

BS 1211:1958 Specification for centrifugally cast (spun) iron pressure pipes for water, gas and sewage

### Description

This Standard includes specification for -

- Pipes with spigot and socket joints cast in either metal or sand moulds,
- Class B, field test pressure 400 ft head of water;
- Class C, 600 ft head of water;
- Class D, 800 ft head of water.

Also standard lengths, internal diameters, hydraulic tests and tests for straightness.

View on Information Provider website

This resource does not cite any other resources.

# BS 1211:1958 Specification for centrifugally cast (spun) iron pressure pipes for water, gas and sewage

I his resource	does not	CITE any	otner	resources.	



#### **Table of Contents**

Print Save Ema	ail		
<u>Feedback</u>			
	_	_	

- Contact usPrivacy policy
- <u>Disclaimer</u>
- Copyright

<u>Feedback</u>