| Skip to main content Skip to primary navigation  Menu                           |             |
|---|-------------|
| <ul><li> Home Home</li><li> About this portal</li><li> Latest updates</li></ul> |             |
| Print Save Email  Resource detail   |             |
| Citations  BS 3832:1991 Specification for wir                                   | e reinforce |

## BS 3832:1991 Specification for wire reinforced rubber hoses and hose assemblies for hydraulic installations

<u>View on Information Provider website</u> {{ linkText }}

Abbreviation

BS 3832:1991

Valid from

20/12/1991

Information provider

**British Standards Institution** 

Author

**British Standards Institution** 

Information type

**British Standard** 

Format

PDF

Cited By

This resource is cited by 1 document (show Citations)

Description

Specifies requirements for hydraulic hoses of internal diameter from 5 mm to 63 mm, operating at temperatures ranging from -40 °C to +100 °C.

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website</u> {{ linkText }}

 $\label{prop:control} \mbox{For assistance with locating previous versions, please contact the information provider.}$ 

This resource is cited by:

## BS 3832:1991 Specification for wire reinforced rubber hoses and hose assemblies for hydraulic installations

This document is CITED BY:

NZS 4332:1997

BS 3832:1991 is cited by NZS 4332:1997 Non-domestic passenger and goods lifts



## BS 3832:1991 Specification for wire reinforced rubber hoses and hose assemblies for hydraulic installations

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

Specifies requirements for hydraulic hoses of internal diameter from 5 mm to 63 mm, operating at temperatures ranging from - 40°C to +100°C.

View on Information Provider website

BS 3832:1991 Specification for wire reinforced rubber hoses and hose assemblies for hydraulic installations

Description

Specifies requirements for hydraulic hoses of internal diameter from 5 mm to 63 mm, operating at temperatures ranging from -40 °C to +100 °C.

View on Information Provider website

This resource does not CITE any other resources.

This resource does not cite any other resources.

## BS 3832:1991 Specification for wire reinforced rubber hoses and hose assemblies for hydraulic installations