

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

BS 6068-2.34:1988 Water quality - Physical, chemical and biochemical methods - Method 2.34: Method for the determination of the chemical oxygen demand

[View on Information Provider website](#)

Abbreviation

BS 6068-2.34:1988

Valid from

31/10/1988

Information provider

Standards New Zealand

Author

British Standards Institution

Information type

British Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

Applicable to most kinds of water having a COD value between 30 and 700 mg/l before dilution. It is not applicable to saline waters containing (after dilution) more than 1000 mg/l of chloride, such as sea and oilfield waters.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

BS 6068-2.34:1988 Water quality - Physical, chemical and biochemical methods - Method 2.34: Method for the determination of the chemical oxygen demand

This document is CITED BY:

- [AS/NZS 4020:2005](#)

BS 6068-2.34:1988 is cited by AS/NZS 4020:2005 Testing of products for use in contact with drinking water

- [BS 6920-2.6:2000](#)

BS 6068-2.34:1988 is cited by BS 6920-2.6:2000 Suitability of non-metallic products for use in contact with water intended for human consumption with regard to their effect on the quality of water. Methods of test. The extraction of metals

Back

BS 6068-2.34:1988 Water quality - Physical, chemical and biochemical methods - Method 2.34: Method for the determination of the chemical oxygen demand

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Applicable to most kinds of water having a COD value between 30 and 700 mg/l before dilution. It is not applicable to saline waters containing (after dilution) more than 1000 mg/l of chloride, such as sea and oilfield waters.

[View on Information Provider website](#)

[BS 6068-2.34:1988 Water quality - Physical, chemical and biochemical methods - Method 2.34: Method for the determination of the chemical oxygen demand](#)

Description

Applicable to most kinds of water having a COD value between 30 and 700 mg/l before dilution. It is not applicable to saline waters containing (after dilution) more than 1000 mg/l of chloride, such as sea and oilfield waters.

[View on Information Provider website](#)

This resource does not cite any other resources.

BS 6068-2.34:1988 Water quality - Physical, chemical and biochemical methods - Method 2.34: Method for the determination of the chemical oxygen demand

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)