

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

BS EN 752-2:1997 Drain and sewer systems outside buildings - Part 2: Performance requirements

[View on Information Provider website](#)

Abbreviation

BS EN 752-2:1997

Valid from

15/03/1997

Information provider

Standards New Zealand

Author

British Standards Institution, European Standardization Organisations

Information type

British Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of BS EN 752 sets out the performance requirements to be taken into account when planning, designing, installing and operating drain and sewer systems that operate essentially under gravity.

This European Standard is applicable to drain and sewer systems, which operate essentially under gravity, from the point where the sewage leaves a building or roof drainage system, or enters a road gully, to the point where it is discharged into a treatment works or receiving water.

Drains and sewers below buildings are included provided that they do not form part of the drainage system of the building.

For assistance with locating previous versions, please contact the information provider.

Notes/comments

BS EN 752-2:1997 is the British Standards version of the European Standard and is referenced as the English language version applicable to this International Standard.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

BS EN 752-2:1997 is the British Standards version of the European Standard and is referenced as the English language version applicable to this International Standard.

This resource is cited by:

BS EN 752-2:1997 Drain and sewer systems outside buildings - Part 2: Performance requirements

This document is CITED BY:

- [BS EN 12056-2:2000](#)

BS EN 752-2:1997 is cited by BS EN 12056-2:2000 Gravity drainage systems inside buildings. Sanitary pipework, layout and calculation

Back

BS EN 752-2:1997 Drain and sewer systems outside buildings - Part 2: Performance requirements

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of BS EN 752 sets out the performance requirements to be taken into account when planning, designing, installing and operating drain and sewer systems that operate essentially under gravity.

This European Standard is applicable to drain and sewer systems, which operate essentially under gravity, from the point where the sewage leaves a building or roof drainage system, or enters a road gully, to the point where it is discharged into a treatment works or receiving water.

Drains and sewers below buildings are included provided that they do not form part of the drainage system of the building.

[View on Information Provider website](#)

[BS EN 752-2:1997 Drain and sewer systems outside buildings - Part 2: Performance requirements](#)

Description

This part of BS EN 752 sets out the performance requirements to be taken into account when planning, designing, installing and operating drain and sewer systems that operate essentially under gravity.

This European Standard is applicable to drain and sewer systems, which operate essentially under gravity, from the point where the sewage leaves a building or roof drainage system, or enters a road gully, to the point where it is discharged into a treatment works or receiving water.

Drains and sewers below buildings are included provided that they do not form part of the drainage system of the building.

[View on Information Provider website](#)

This resource does not cite any other resources.

BS EN 752-2:1997 Drain and sewer systems outside buildings - Part 2: Performance requirements

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)