

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

BS EN ISO 10523:2012 Water quality. Determination of pH

[View on Information Provider website](#)

Abbreviation

BS EN ISO 10523:2012

Valid from

30/06/2010

Information provider

SAI Global

Author

British Standards Institution, European Standardization Organisations, International Organisation for Standardization

Information type

British Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard specifies a method for determining the pH value in rain, drinking and mineral waters, bathing waters, surface and ground waters, as well as municipal and industrial waste waters, and liquid sludge, within the range pH 2 to pH 12 with an ionic strength below $I = 0,3 \text{ mol/kg}$ (conductivity at $25 \text{ }^\circ\text{C} < 2 \text{ 000 mS/m}$) solvent and in the temperature range $0 \text{ }^\circ\text{C}$ to $50 \text{ }^\circ\text{C}$.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

BS EN ISO 10523:2012 Water quality. Determination of pH

This document is CITED BY:

- [BS 6920-2.6:2000](#)

BS EN ISO 10523:2012 is cited by BS 6920-2.6:2000 Suitability of non-metallic products for use in contact with water intended for human consumption with regard to their effect on the quality of water. Methods of test. The extraction of metals

Back

BS EN ISO 10523:2012 Water quality. Determination of pH

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies a method for determining the pH value in rain, drinking and mineral waters, bathing waters, surface and ground waters, as well as municipal and industrial waste waters, and liquid sludge, within the range pH 2 to pH 12 with an ionic strength below $I = 0,3 \text{ mol/kg}$ (conductivity at $25 \text{ }^\circ\text{C} < 2 \text{ 000 mS/m}$) solvent and in the temperature range $0 \text{ }^\circ\text{C}$ to $50 \text{ }^\circ\text{C}$.

[View on Information Provider website](#)

[BS EN ISO 10523:2012 Water quality. Determination of pH](#)

Description

This Standard specifies a method for determining the pH value in rain, drinking and mineral waters, bathing waters, surface and ground waters, as well as municipal and industrial waste waters, and liquid sludge, within the range pH 2 to pH 12 with an ionic strength below $I = 0,3 \text{ mol/kg}$ (conductivity at $25 \text{ }^\circ\text{C} < 2 \text{ 000 mS/m}$) solvent and in the temperature range $0 \text{ }^\circ\text{C}$ to $50 \text{ }^\circ\text{C}$.

[View on Information Provider website](#)

This resource does not cite any other resources.

BS EN ISO 10523:2012 Water quality. Determination of pH

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)