

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Print](#) [Save](#) [Email](#)

[Resource detail](#)

[Citations](#)

## BS EN ISO 75-2:2004 Plastics - Determination Of Temperature Of Deflection Under Load - Part 2: Plastics and ebonite

[View on Information Provider website](#) [{{ linkText }}](#)

Abbreviation

BS EN ISO 75-2:2004

Valid from

15/05/2004

---

Information provider

Standards New Zealand

Author

International Organization for Standardization,  
European Standardization Organisations,  
British Standards Institution

Information type

European Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

Description

BS EN ISO 75-2:2013 specifies three methods, using different values of constant flexural stress, which can be used for the determination of the temperature of deflection under load of plastics (including filled plastics and fibre-reinforced plastics in which the fibre length, prior to processing, is up to 7,5 mm) and ebonite:

- method A, using a flexural stress of 1,80 MPa;
- method B, using a flexural stress of 0,45 MPa;
- method C, using a flexural stress of 8,00 MPa.

BS EN ISO 75-2:2004 is identical to EN ISO 75-2:2004

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [{{ linkText }}](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# BS EN ISO 75-2:2004 Plastics - Determination Of Temperature Of Deflection Under Load - Part 2: Plastics and ebonite

This document is CITED BY:

- [BS EN 13121-3:2008](#)

BS EN ISO 75-2:2004 is cited by BS EN 13121-3:2008 GRP tanks and vessels for use above ground. Design and workmanship

Back

# BS EN ISO 75-2:2004 Plastics - Determination Of Temperature Of Deflection Under Load - Part 2: Plastics and ebonite

Show what documents this resource is CITED BY

Show what documents this resource CITES

## Description

BS EN ISO 75-2:2013 specifies three methods, using different values of constant flexural stress, which can be used for the determination of the temperature of deflection under load of plastics (including filled plastics and fibre-reinforced plastics in which the fibre length, prior to processing, is up to 7,5 mm) and ebonite:

- method A, using a flexural stress of 1,80 MPa;
- method B, using a flexural stress of 0,45 MPa;
- method C, using a flexural stress of 8,00 MPa.

BS EN ISO 75-2:2004 is identical to EN ISO 75-2:2004

[View on Information Provider website](#)

[BS EN ISO 75-2:2004 Plastics - Determination Of Temperature Of Deflection Under Load - Part 2: Plastics and ebonite](#)

## Description

BS EN ISO 75-2:2013 specifies three methods, using different values of constant flexural stress, which can be used for the determination of the temperature of deflection under load of plastics (including filled plastics and fibre-reinforced plastics in which the fibre length, prior to processing, is up to 7,5 mm) and ebonite:

- method A, using a flexural stress of 1,80 MPa;
- method B, using a flexural stress of 0,45 MPa;
- method C, using a flexural stress of 8,00 MPa.

BS EN ISO 75-2:2004 is identical to EN ISO 75-2:2004

[View on Information Provider website](#)

This resource does not cite any other resources.

# BS EN ISO 75-2:2004 Plastics - Determination Of Temperature Of Deflection Under Load - Part 2: Plastics and ebonite

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)