

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

Asphaltech Rubberised Membrane System

[View on Information Provider website](#) [Download this resource \(PDF, 386KB\)](#)

Abbreviation

CM70010

Valid from

19/03/2019

Information provider

Ministry of Business, Innovation and Employment

Information type

Product Certificate (CodeMark)

Format

PDF

Description

The Asphaltech Rubberised Membrane System is a polymer modified bitumen applied over insulation board or a timber or concrete structural substrate in two layers with a nominal thickness of 6mm, and protection membrane to give a total thickness of up to 10mm.

Scope

This product certificate covers the use of the Asphaltech Rubberised Membrane System, as a waterproof roofing membrane.

The Asphaltech Rubberised Membrane System may be used where the minimum gradient of the substrate structure is completely flat (less than 1:80) including nominally zero pitch.

The Asphaltech Rubberised Membrane System can withstand maintenance pedestrian traffic.

Asphaltech Rubberised Membrane System provides a suitable substrate for external pavers, tiles or concrete for pedestrian traffic, and for pavers or tiles on paver supports, for use on terraces, balconies or podia.

Asphaltech Rubberised Membrane System may be used as part of a green roof system.

Asphaltech Rubberised Membrane System may be used as part of an inverted insulated roof.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 386KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Asphaltech Rubberised Membrane System

This document is not CITED BY any other resources:

Back

Asphaltech Rubberised Membrane System

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

The Asphaltech Rubberised Membrane System is a polymer modified bitumen applied over insulation board or a timber or concrete structural substrate in two layers with a nominal thickness of 6mm, and protection membrane to give a total thickness of up to 10mm.

[View on Information Provider website](#) [Download this resource \(PDF, 386KB\)](#)

[Asphaltech Rubberised Membrane System](#)

Description

The Asphaltech Rubberised Membrane System is a polymer modified bitumen applied over insulation board or a timber or concrete structural substrate in two layers with a nominal thickness of 6mm, and protection membrane to give a total thickness of up to 10mm.

[View on Information Provider website](#) [Download this resource \(PDF, 386KB\)](#)

This resource does not cite any other resources.

Asphaltech Rubberised Membrane System

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)