

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print [Save](#) Email

[Resource detail](#)

[Citations](#)

## Fastwrap FlameSpec HW Roof Underlay

[View on Information Provider website](#) [Download this resource \(PDF, 225KB\)](#)

### Abbreviation

CM70049

### Valid from

28/10/2019

---

### Information provider

Ministry of Business, Innovation and Employment

### Author

Bureau Veritas

### Information type

Product Certificate (CodeMark)

### Format

PDF

---

### Description

Fastwrap FlameSpec HW Roof Underlay is a synthetic building underlay for use under roof claddings.

The product consists of a micro-porous water resistant film laminated to two layers of Non-woven spun-bonded polyolefin.

Fastwrap FlameSpec HW Roof Underlay is supplied in rolls 1.350m wide x 55.56m long, and is printed with the Fastwrap logo repeated along the length of the roll.

### Scope

Subject to the following conditions and limitations

1. Fastwrap FlameSpec HW Roof Underlay must be installed in accordance with the Fastwrap FlameSpec HW Roof Underlay brochure V1 (15/08/2018).
2. Fastwrap FlameSpec HW Roof Underlay must be supported by a corrosion resistant material
3. Fastwrap FlameSpec HW Roof Underlay must not be exposed to weather or UV light for more than 7 days before being covered by the roof cladding.
4. Fastwrap FlameSpec HW Roof Underlay may only be used as a roof underlay on buildings:
  - within the limitations of NZBC Acceptable Solution E2/AS1 (Amendment 9, Effective 27 June 2019), Paragraph 1.1 with regards to building height and floor plan area; and
  - situated in NZS 3604:2011 Building Wind Zones up to, and including Extra High; and
  - with roof pitch 10 degrees or greater; and
  - with masonry tile (B2.3.1 (b) applies), metal tile or profiled metal roof cladding (B2.3.2(b) applies)

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 225KB\)](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

## Fastwrap FlameSpec HW Roof Underlay

This document is not CITED BY any other resources:

Back

## Fastwrap FlameSpec HW Roof Underlay

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Fastwrap FlameSpec HW Roof Underlay is a synthetic building underlay for use under roof claddings.

The product consists of a micro-porous water resistant film laminated to two layers of Non-woven spun-bonded polyolefin.

Fastwrap FlameSpec HW Roof Underlay is supplied in rolls 1.350m wide x 55.56m long, and is printed with the Fastwrap logo repeated along the length of the roll.

[View on Information Provider website](#) [Download this resource \(PDF, 225KB\)](#)

[Fastwrap FlameSpec HW Roof Underlay](#)

### Description

Fastwrap FlameSpec HW Roof Underlay is a synthetic building underlay for use under roof claddings.

The product consists of a micro-porous water resistant film laminated to two layers of Non-woven spun-bonded polyolefin.

Fastwrap FlameSpec HW Roof Underlay is supplied in rolls 1.350m wide x 55.56m long, and is printed with the Fastwrap logo repeated along the length of the roll.

[View on Information Provider website](#) [Download this resource \(PDF, 225KB\)](#)

This resource does not cite any other resources.

## Fastwrap FlameSpec HW Roof Underlay

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)

- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)