

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

Novabond F.C. 200

[View on Information Provider website](#) [Download this resource \(PDF, 220KB\)](#)

Abbreviation
CM70058
Valid from
19/12/2019

Information provider
Ministry of Business, Innovation and Employment
Author
Bureau Veritas
Information type
Product Certificate (CodeMark)
Format
PDF

Description

Novabond FC 200 is a plastomeric modified bitumen torch-on waterproofing membrane (APP).

Novabond is available in thicknesses of 3 and 4mm and comes in 10m x 1m rolls.

Novabond F.C. 200 is used for waterproofing basement retaining walls and floors.

Scope

Subject to the following conditions and limitations:

1. Shall only be applied to buildings subject to non-specific design under floor slabs complying with NZS 3604:2011 Timber-framed buildings; and
2. Shall only be applied behind concrete masonry basement walls and under floor slabs complying with NZS 4229:1999 Concrete masonry buildings not requiring specific engineering; and
3. Shall only be applied to buildings subject to specific design with substrates of in situ or precast concrete complying with NZS 3101:2006 Concrete Structures, or concrete masonry complying with NZS 4230:2004 Design of reinforced concrete masonry structures.
4. Novabond F.C. 200 shall only be stored, installed and maintained as per the Jaydex Application Guide Novater V3, November 2019.
5. Installation shall be by Jaydex licensed applicators.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 220KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Novabond F.C. 200

This document is not CITED BY any other resources:

Back

Novabond F.C. 200

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Novabond FC 200 is a plastomeric modified bitumen torch-on waterproofing membrane (APP).

Novabond is available in thicknesses of 3 and 4mm and comes in 10m x 1m rolls.

Novabond F.C. 200 is used for waterproofing basement retaining walls and floors.

[View on Information Provider website](#) [Download this resource \(PDF, 220KB\)](#)

[Novabond F.C. 200](#)

Description

Novabond FC 200 is a plastomeric modified bitumen torch-on waterproofing membrane (APP).

Novabond is available in thicknesses of 3 and 4mm and comes in 10m x 1m rolls.

Novabond F.C. 200 is used for waterproofing basement retaining walls and floors.

[View on Information Provider website](#) [Download this resource \(PDF, 220KB\)](#)

This resource does not cite any other resources.

Novabond F.C. 200

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)