

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12

[View on Information Provider website](#) [Download this resource \(PDF, 409KB\)](#)

Abbreviation

CM70064

Valid from

30/01/2020

Information provider

Ministry of Business, Innovation and Employment

Author

Bureau Veritas

Information type

Product Certificate (CodeMark)

Format

PDF

Description

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12, are high-density particleboard panels. The supplied glue bonds the panels together to form a continuous flooring membrane and provides an effective seal against moisture. The floors are suitable for use as a floor diaphragm within the scope of NZS 3604:2011 Timber framed buildings.

Scope

Subject to the following conditions and limitations:

1. Kopine flooring systems must be laid in accordance with the Kopine Installation Guide and Technical Specifications (May 2018).
2. The subfloor must be ventilated and protected from external moisture
3. The flooring must be protected by a membrane or other impervious finish when installed in wet and splash areas.
4. The moisture content of the flooring must be no more than 18% before sealing or covering with a flooring product.
5. Kopine flooring systems are suitable for concentrated loads up to 180kg or uniformly distributed loads up to 200kg/m2. Loads greater than these must be specifically designed.
6. Exposure to weather should be kept to a minimum, and no more than three months.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 409KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12

This document is not CITED BY any other resources:

Back

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12, are high-density particleboard panels. The supplied glue bonds the panels together to form a continuous flooring membrane and provides an effective seal against moisture. The floors are suitable for use as a floor diaphragm within the scope of NZS 3604:2011 Timber framed buildings.

[View on Information Provider website](#) [Download this resource \(PDF, 409KB\)](#)

[Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12](#)

Description

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12, are high-density particleboard panels. The supplied glue bonds the panels together to form a continuous flooring membrane and provides an effective seal against moisture. The floors are suitable for use as a floor diaphragm within the scope of NZS 3604:2011 Timber framed buildings.

[View on Information Provider website](#) [Download this resource \(PDF, 409KB\)](#)

This resource does not cite any other resources.

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)