

Menu

- [Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

CSR Hebel PowerPanel50

[Download this resource \(PDF, 182KB\)](#)

Abbreviation

CMA-CM40064 (Rev4)

Valid from

21/08/2013

Information provider

Ministry of Business, Innovation and Employment

Author

CertMark International Pty Ltd T/A CertMark New Zealand

Information type

Product Certificate (CodeMark)

Format

PDF

Description

CSR Hebel PowerPanel50 - 50mm thick lightweight steel-reinforced Autoclaved Aerated Concrete (AAC) panels are mounted vertically on cavity battens, screw fixed to the external load bearing wall. The exterior panel face is then sealed using a plastered rendered coating.

- Panel in-service density: 510kg/m³
- Panel sizes: Up to 600mm wide and up to 2400mm long

Scope

Product Use:

- A non-loadbearing external wall cladding system that can be installed on timber or steel load

bearing wall frames.

For assistance with locating previous versions, please contact the information provider.

[Download this resource \(PDF, 182KB\)](#) `{{ linkText }}`

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

CSR Hebel PowerPanel50

This document is not CITED BY any other resources:

Back

CSR Hebel PowerPanel50

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

CSR Hebel PowerPanel50 - 50mm thick lightweight steel-reinforced Autoclaved Aerated Concrete (AAC) panels are mounted vertically on cavity battens, screw fixed to the external load bearing wall. The exterior panel face is then sealed using a plastered rendered coating.

- Panel in-service density: 510kg/m³
- Panel sizes: Up to 600mm wide and up to 2400mm long

[Download this resource \(PDF, 182KB\)](#)

[CSR Hebel PowerPanel50](#)

Description

CSR Hebel PowerPanel50 - 50mm thick lightweight steel-reinforced Autoclaved Aerated Concrete (AAC) panels are mounted vertically on cavity battens, screw fixed to the external load bearing wall. The exterior panel face is then sealed using a plastered rendered coating.

- Panel in-service density: 510kg/m³
- Panel sizes: Up to 600mm wide and up to 2400mm long

[Download this resource \(PDF, 182KB\)](#)

This resource does not cite any other resources.

CSR Hebel PowerPanel50

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)