

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

Performance of mid-rise cladding systems, EM7 (May 2019)

[Download this resource \(PDF, 365KB\)](#)

Abbreviation

EM7 (May 2019)

Version

Version 2

Valid from

01/05/2019

Information provider

BRANZ Limited

Information type

Evaluation method

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Cites

[This resource cites 4 documents \(show Citations\)](#)

Description

This evaluation method (EM7) represents a series of tests from **AS/NZS 4284:2008 Testing of building facades**, with specific nominated values for the performance levels.

EM7 provides a means of assessing the weathertightness-oriented performance of generic domestic-oriented external wall cladding systems for use on buildings between 10m and 25m in height and expects that a drained and ventilated cavity is used as part of the cladding design.

The aim is to provide a test with a consistent set of parameters for use in the design of claddings for mid-rise building.

Scope

The scope of EM7 is restricted to buildings that:

- have a height measured from the lowest ground level adjacent to the building to the highest point of the roof (except for chimneys, aerials and the like) of 25m or less
- have cladding systems exposed to a specific peak positive SLS air pressure of up to 2.25kPa (ULS 3.2kPa)
- have claddings that include a drained and ventilated cavity of 20mm minimum depth with an inter-storey horizontal drainage joint every 2 floors, or 7.0m, and minimum ventilation openings of 1000mm²/m

- include window and door units that are manufactured to comply with the relevant pressures and inter-storey deflections
- have inter-storey deflections design for up to +15mm of horizontal in-plane movement during seismic SLS events assuming a 3m inter-storey height (height/200)
- have cladding supported on lightweight framing (expected to be timber or light steel framing) with studs at centres no greater than 600mm that is structurally connected to the floor at each level of the building - this evaluation method is not intended to be used with infill framing that is isolated from structural movement of the building
- have a rigid building underlay affixed to the framing

Previous versions:

For assistance with locating previous versions, please contact the information provider.

[Download this resource \(PDF, 365KB\)](#) {{ linkText }}

Previous versions

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

Performance of mid-rise cladding systems, EM7 (May 2019)

This document is CITED BY:

- [E2/VM2 \(First Edition\)](#)

EM7 (May 2019) is cited by Verification Method E2/VM2: External Moisture from 27/06/2019

Back

Performance of mid-rise cladding systems, EM7 (May 2019)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This evaluation method (EM7) represents a series of tests from **AS/NZS 4284:2008 Testing of building facades**, with specific nominated values for the performance levels.

EM7 provides a means of assessing the weathertightness-oriented performance of generic domestic-oriented external wall cladding systems for use on buildings between 10m and 25m in height and expects that a drained and ventilated cavity is used as part of the cladding design.

The aim is to provide a test with a consistent set of parameters for use in the design of claddings for mid-rise building.

[Download this resource \(PDF, 365KB\)](#)

[Performance of mid-rise cladding systems, EM7 \(May 2019\)](#)

Description

This evaluation method (EM7) represents a series of tests from **AS/NZS 4284:2008 Testing of building facades**, with specific nominated values for the performance levels.

EM7 provides a means of assessing the weathertightness-oriented performance of generic domestic-oriented external wall cladding systems for use on buildings between 10m and 25m in height and expects that a drained and ventilated cavity is used as part of the cladding design.

The aim is to provide a test with a consistent set of parameters for use in the design of claddings for mid-rise building.

[Download this resource \(PDF, 365KB\)](#)

This resource cites:

Performance of mid-rise cladding systems, EM7 (May 2019)

This document CITES:

New Zealand Standards

- [AS/NZS 1170.2:2011](#)

EM7 (May 2019) cites AS/NZS 1170.2:2011 Structural Design Actions - Wind Actions

- [AS/NZS 4284:2008](#)

EM7 (May 2019) cites AS/NZS 4284:2008 Testing of building facades

Other

- [AAMA 508-14](#)

EM7 (May 2019) cites AAMA 508-14 Voluntary Test Method and Specification for Pressure Equalized Rain Screen Wall Cladding Systems.

- [ASTM E1677-11](#)

EM7 (May 2019) cites ASTM E1677-11 Standard Specification for Air Barrier (AB) Material or System for Low-Rise Framed Building Walls

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)