

### ER53 Measuring the extent of thermal bridging in external timber - framed walls in New Zealand

<u>View on Information Provider website Download this resource (PDF, 3.4MB)</u> {{ linkText }}

Abbreviation ER53(2020) Valid from 01/09/2020

Information provider
BRANZ Limited
Author
Verney Ryan, Guy Penny, Jane Cuming, Ian Mayes and Graeme Baker
Information type
Study report
Format
PDF

#### Description

This report shares the results and findings of a project to investigate the extent of thermal bridging in external timber-framed walls of new builds. The project took a case study approach to investigate the percentage of framing in 47 newly constructed dwellings from Auckland, Christchurch, Wellington and Hamilton.

The results show that the average percentage of timber framing compared to the area of the wall is above 34%. This is much higher than the 14-18% framing content generally assumed by both regulators and the industry. The results strongly indicate that the content of timber framing in external walls in residential new builds is at such high levels that the increased thermal bridging compromises the performance of walls and may mean that designed R-values are not being achieved.

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website Download this resource (PDF, 3.4MB)</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

## ER53 Measuring the extent of thermal bridging in external timber - framed walls in New Zealand

This document is not CITED BY any other resources:

Back

# ER53 Measuring the extent of thermal bridging in external timber - framed walls in New Zealand

Show what documents this resource is CITED BY

Show what documents this resource CITES

#### Description

This report shares the results and findings of a project to investigate the extent of thermal bridging in external timber-framed walls of new builds. The project took a case study approach to investigate the percentage of framing in 47 newly constructed dwellings from Auckland, Christchurch, Wellington and Hamilton.

The results show that the average percentage of timber framing compared to the area of the wall is above 34%. This is much higher than the 14-18% framing content generally assumed by both regulators and the industry. The results strongly indicate that the content of timber framing in external walls in residential new builds is at such high levels that the increased thermal bridging compromises the performance of walls and may mean that designed R-values are not being achieved.

View on Information Provider website Download this resource (PDF, 3.4MB)

ER53 Measuring the extent of thermal bridging in external timber - framed walls in New Zealand

#### Description

This report shares the results and findings of a project to investigate the extent of thermal bridging in external timber-framed walls of new builds. The project took a case study approach to investigate the percentage of framing in 47 newly constructed dwellings from Auckland, Christchurch, Wellington and Hamilton.

The results show that the average percentage of timber framing compared to the area of the wall is above 34%. This is much higher than the 14-18% framing content generally assumed by both regulators and the industry. The results strongly indicate that the content of timber framing in external walls in residential new builds is at such high levels that the increased thermal bridging compromises the performance of walls and may mean that designed R-values are not being achieved.

View on Information Provider website Download this resource (PDF, 3.4MB)

This resource does not cite any other resources.

# ER53 Measuring the extent of thermal bridging in external timber - framed walls in New Zealand

This resource does not CITE any other resources.	
Back	
Table of Contents	
Print Save Email Feedback	
<ul> <li>Contact us</li> <li>Privacy policy</li> <li>Disclaimer</li> <li>Copyright</li> </ul>	
Essetheral.	
Feedback	