

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)

[Citations](#)

ETSI EN 300 220-1 (2000) - Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical charact

[View on Information Provider website](#)

Abbreviation

ETSI EN 300 220-1 (2000)

Valid from

09/01/2000

Information provider

TechStreet

Author

European Telecommunications Standards Institute

Information type

European Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

The present document applies to short range device radio transmitters and receivers:

- 1) transmitters in the range from 25 MHz to 1 000 MHz and with power levels ranging up to 500 mW;
- 2) receivers in the range from 25 MHz to 1 000 MHz.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ETSI EN 300 220-1 (2000) - Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the

25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical charact

This document is CITED BY:

- [BS 7273-4:2007](#)

ETSI EN 300 220-1 (2000) is cited by BS 7273-4:2007 Code of practice for the operation of fire protection measures.
Actuation of release mechanisms for doors

Back

ETSI EN 300 220-1 (2000) - Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical charact

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

The present document applies to short range device radio transmitters and receivers:

- 1) transmitters in the range from 25 MHz to 1 000 MHz and with power levels ranging up to 500 mW;
- 2) receivers in the range from 25 MHz to 1 000 MHz.

[View on Information Provider website](#)

[ETSI EN 300 220-1 \(2000\) - Electromagnetic compatibility and Radio spectrum Matters \(ERM\); Short Range Devices \(SRD\); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical charact](#)

Description

The present document applies to short range device radio transmitters and receivers:

- 1) transmitters in the range from 25 MHz to 1 000 MHz and with power levels ranging up to 500 mW;
- 2) receivers in the range from 25 MHz to 1 000 MHz.

[View on Information Provider website](#)

This resource does not cite any other resources.

ETSI EN 300 220-1 (2000) - Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical charact

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)