

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ETSI EN 300 220-2 (2000) ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary paramet

[View on Information Provider website](#)

Abbreviation
ETSI EN 300 220-2 (2000)
Valid from
09/01/2000

Information provider
TechStreet
Author
European Telecommunications Standards Institute
Information type
European Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

The present document applies to short range device radio transmitters and receivers as described in the scope of EN 300 220-1 [2].

The present document is intended to cover the provisions of Article 3.2 of Directive 1999/5/EC [1] (R&TTE Directive), which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ETSI EN 300 220-2 (2000) ElectroMagnetic Compatibility and Radio Spectrum

Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary paramet

This document is CITED BY:

- [BS 7273-4:2007](#)

ETSI EN 300 220-2 (2000) is cited by BS 7273-4:2007 Code of practice for the operation of fire protection measures. Actuation of release mechanisms for doors

Back

ETSI EN 300 220-2 (2000) ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary paramet

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

The present document applies to short range device radio transmitters and receivers as described in the scope of EN 300 220-1 [2].

The present document is intended to cover the provisions of Article 3.2 of Directive 1999/5/EC [1] (R&TTE Directive), which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

[View on Information Provider website](#)

[ETSI EN 300 220-2 \(2000\) ElectroMagnetic Compatibility and Radio Spectrum Matters \(ERM\); Short Range Devices \(SRD\); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary paramet](#)

Description

The present document applies to short range device radio transmitters and receivers as described in the scope of EN 300 220-1 [2].

The present document is intended to cover the provisions of Article 3.2 of Directive 1999/5/EC [1] (R&TTE Directive), which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

[View on Information Provider website](#)

This resource does not cite any other resources.

ETSI EN 300 220-2 (2000) ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary paramet

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)