

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

## Acceptable Solution F6/AS1: Visibility in Escape Routes

Table of Contents

[View on Information Provider website](#) [Download this resource \(PDF, 472KB\)](#)

{{ linkText }}

This resource is no longer current. The current version is [F6/AS1 \(Third Edition, Amendment 4\)](#)

Abbreviation

F6/AS1

Amendment

3

Version

Third Edition, Amendment 3

Valid to

30/05/2017

Valid from

14/02/2014

Replaces

[F6/AS1 \(Third Edition, Amendment 2\)](#)

Replaced By

[F6/AS1 \(Third Edition, Amendment 4\)](#)

---

Information provider

Ministry of Business, Innovation and Employment

Information type

Acceptable Solution

Format

PDF

---

Cites

[This resource cites 6 documents \(show Citations\)](#)

---

## Description

Acceptable Solution F6/AS1 provides a means of compliance with Building Code Clause F6 Visibility in Escape Routes. Building Code Clause F6 provides for safety features for escape routes during failure of the main lighting. It ensures specified features in escape routes must be made reasonably visible during failure of main lighting. It applies to buildings in specific risk groups and particular locations in buildings (such as areas where dangerous machinery is installed, or any part of an escape route designed for use at any time by more than 250 people). It ensures systems for visibility operate within given percentages of their design levels and within given timeframes.

## Scope

This Acceptable Solution applies to situations where emergency lighting is used as the sole means of meeting the performance requirements of Clause F6. This Acceptable Solution does not apply to lighting that is essential to maintain safe working conditions.

## Previous versions:

[F6/AS1 \(Third Edition, Amendment 2\)](#)

For assistance with locating previous versions, please contact the information provider.

[Table of Contents](#) [View on Information Provider website](#) [Download this resource \(PDF, 472KB\)](#)

{{ linkText }}

[Previous versions](#)

[F6/AS1 Amendment 2 Third Edition, Amendment 2](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

# Acceptable Solution F6/AS1: Visibility in Escape Routes

This document is not CITED BY any other resources:

[Back](#)

# Acceptable Solution F6/AS1: Visibility in Escape Routes

[Show what documents this resource is CITED BY](#)

[Show what documents this resource CITES](#)

#### Description

Acceptable Solution F6/AS1 provides a means of compliance with Building Code Clause F6 Visibility in Escape Routes. Building Code Clause F6 provides for safety features for escape routes during failure of the main lighting. It ensures specified features in escape routes must be made reasonably visible during failure of main lighting. It applies to buildings in specific risk groups and particular locations in buildings (such as areas where dangerous machinery is installed, or any part of an escape route designed for use at any time by more than 250 people). It ensures systems for visibility operate within given percentages of their design levels and within given timeframes.

[View on Information Provider website](#) [Download this resource \(PDF, 472KB\)](#)

#### [Acceptable Solution F6/AS1: Visibility in Escape Routes](#)

This resource is no longer current. The current version is [F6/AS1 \(Third Edition, Amendment 4\)](#)

#### Description

Acceptable Solution F6/AS1 provides a means of compliance with Building Code Clause F6 Visibility in Escape Routes. Building Code Clause F6 provides for safety features for escape routes during failure of the main lighting. It ensures specified features in escape routes must be made reasonably visible during failure of main lighting. It applies to buildings in specific risk groups and particular locations in buildings (such as areas where dangerous machinery is installed, or any part of an escape route designed for use at any time by more than 250 people). It ensures systems for visibility operate within given percentages of their design levels and within given timeframes.

[View on Information Provider website](#) [Download this resource \(PDF, 472KB\)](#)

**This resource cites:**

## Acceptable Solution F6/AS1: Visibility in Escape Routes

**This document CITES:**

#### New Zealand Standards

- [AS/NZS 1680.1:2006](#)

F6/AS1 cites AS/NZS 1680.1:2006 Interior and workplace lighting - Part 1: General principles and recommendations from 18/10/2007

- [AS/NZS 2293.2:1995](#)

F6/AS1 cites AS/NZS 2293.2:1995 Emergency evacuation lighting for buildings - Inspection and maintenance from 18/10/2007

- [NZS 4332:1997](#)

F6/AS1 cites NZS 4332:1997 Non-domestic passenger and goods lifts from 18/10/2007

- [NZE 6104:1981](#)

F6/AS1 cites NZS 6104:1981 Specification for emergency electricity supply in buildings from 01/06/2001

#### Australian Standards

- [AS 2293.1-2005](#)

F6/AS1 cites AS 2293.1-2005 Emergency escape lighting and exit signs for buildings. Part 1: System design, installation and operation from 18/10/2007

- [AS 2293.3-2005](#)

F6/AS1 cites AS 2293.3-2005 Emergency escape lighting and exit signs for buildings. Part 3: Emergency escape luminaires and exit signs from 18/10/2007

Back

Close

#### Table of Contents

## References

## Definitions

## Acceptable Solution F6/AS1

### 1.1 Scope

### 1.2 Location

### 1.3 Illuminance

### 1.4 Method of Measurement

### 1.5 Start-up and Light Output

### 1.6 Duration

### 1.7 Documentation

### 1.8 Installation, Maintenance and Equipment

## Appendix A – Occupant Densities

## Appendix B – Modifications to AS 2293.1: 2005 and AS 2293.3: 2005

## Appendix C – Modifications to NZS 6104

## Appendix D – Measurement of escape route travel distance

### Index

[Save](#)

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)