| Skip to main content Skip to primary navigation | |
|--|--|
| Menu | |
| Home Home About this portal Latest updates | |
| Print Save Email Resource detail Citations | |

Verification Method G13/VM4: Foul Water: On-Site Disposal

Table of Contents

View on Information Provider website Download this resource (PDF, 2.7MB) {{ linkText }}

This resource is no longer current. The current version is G13/VM4 (Second Edition, Amendment 8)

Abbreviation G13/VM4 Amendment 7 Version Second Edition, Amendment 7 Valid from 30/11/2018

Information provider Ministry of Business, Innovation and Employment Information type Verification Method Format PDF

Cites

This resource cites 1 document (show Citations)

Description

Verification Method G13/VM4 provides a means of compliance with Building Code Clause G13 Foul Water for onsite disposal. Code clause G13 requires the safe disposal of foul water to prevent illness and the loss of amenity due to odour and accumulated matter.

Scope

This document describes the design methods for systems used for the collection, storage, treatment and disposal of foul water. A design method and construction details given in sections 5.1 to 5.5 and 6.1 to 6.2 of AS/NZS 1547: 2012 (and the appendices referred to in these sections), for the treatment of domestic foul water for flow rates up to a maximum 14,000 litres/week from a population equivalent of up to 10 persons, may be verified as satisfying the performance criteria of G13 Foul Water.

Previous versions:

G13/VM4 (Second edition, amendment 6) G13/VM4 (Second Edition, Amendment 5) G13/VM4 (Second Edition, Amendment 4) G13/VM4 (Second Edition, Amendment 3)

For assistance with locating previous versions, please contact the information provider.

Notes/comments

This Amendment includes Alterations on:

- page 8 References
- page 33 G13/AS1 7.1.3
- page 50 G13/AS2 6.1.3
- page 51 G13/AS3 2.0.1

 Table of Contents
 View on Information Provider website Download this resource (PDF, 2.7MB)
 {{ linkText }}

Previous versions

G13/VM4 Amendment 5 Second edition, amendment 6 G13/VM4 Amendment 5 Second Edition, Amendment 5 G13/VM4 Amendment 4 Second Edition, Amendment 4 G13/VM4 Amendment 3 Second Edition, Amendment 3

For assistance with locating previous versions, please contact the information provider.

This Amendment includes Alterations on:

- page 8 References
- page 33 G13/AS1 7.1.3
- page 50 G13/AS2 6.1.3
- page 51 G13/AS3 2.0.1

This resource is not cited by any other resources.

Verification Method G13/VM4: Foul Water: On-Site Disposal

This document is not CITED BY any other resources:

Back

Verification Method G13/VM4: Foul Water: On-Site Disposal

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Verification Method G13/VM4 provides a means of compliance with Building Code Clause G13 Foul Water for onsite disposal. Code clause G13 requires the safe disposal of foul water to prevent illness and the loss of amenity due to odour and accumulated matter.

View on Information Provider website Download this resource (PDF, 2.7MB)

Verification Method G13/VM4: Foul Water: On-Site Disposal

This resource is no longer current. The current version is G13/VM4 (Second Edition, Amendment 8)

Description

Verification Method G13/VM4 provides a means of compliance with Building Code Clause G13 Foul Water for onsite disposal. Code clause G13 requires the safe disposal of foul water to prevent illness and the loss of amenity due to odour and accumulated matter.

View on Information Provider website Download this resource (PDF, 2.7MB)

This resource cites:

Verification Method G13/VM4: Foul Water: On-Site Disposal

This document CITES:

New Zealand Standards

• AS/NZS 1547:2012

G13/VM4 cites AS/NZS 1547:2012 On-site domestic wastewater management from 14/02/2014

| Back |
|-------|
| Close |

Table of Contents

References

- Definitions
- Verification Method G13/VM1 Sanitary Plumbing
- **1.0 Sanitary Plumbing**
- Acceptable Solution G13/AS1 Sanitary Plumbing
- 1.0 Scope
- 2.0 Materials
- 2.1 Pipes, traps and fittings
- 3.0 Water Traps
- 3.1 Water trap requirements
- 3.2 Water trap dimensions
- 3.3 Water trap location
- **3.4 Floor outlets**
- 4.0 Discharge Pipes
- 4.1 Layout
- 4.2 Access for cleaning
- 4.3 Diameter
- 4.4 Gradient
- 4.5 Fixture discharge pipes serving waste water fixtures
- 4.6 Fixture discharge pipes serving soil fixtures
- 4.7 Discharge stacks
- 5.0 Venting

- **5.1 Venting required**
- 5.2 Vent pipes
- 5.3 Diameter of vent pipes
- 5.4 Gradient of vent pipes
- 5.5 Connection of vents to fixture discharge pipes
- 5.6 Discharge stack and relief vents
- 5.7 Termination of open vent pipes
- 5.8 Air admittance valves
- 6.0 Installation
- 6.1 Jointing methods
- 6.2 Pipe supports
- 6.3 Thermal movement
- 6.4 Fire separation
- 7.0 Watertightness
- 7.1 Test methods
- Verification Method G13/VM2 Drainage
- 1.0 Drainage
- Acceptable Solution G13/AS2 Drainage
- 1.0 Scope
- 2.0 Materials
- 2.1 Fill materials
- 3.0 Design
- 3.1 Bends
- **3.2 Junctions**
- 3.3 Gully traps
- 3.4 Grease traps
- 3.5 Gradient of drains

- 3.6 Diameter of drains
- 4.0 Drain Ventilation
- 4.1 Ventilation requirements
- 4.2 Diameter of drain vent pipe
- 5.0 Installation
- 5.1 Jointing
- **5.2 Construction**
- **5.3 Construction methods**
- 5.4 Trench width
- 5.5 Placing and compacting
- 5.6 Proximity of trench to building
- 5.7 Access points
- 5.8 Additional requirements for drains installed under buildings
- 5.9 Access to drains under buildings
- 5.10 Disused drains
- 6.0 Watertightness
- 6.1 Testing
- Acceptable Solution G13/AS3 Plumbing and Drainage
- 1.0 Installation of uPVC pipe
- 2.0 AS/NZS 3500.2

Verification Method G13/VM4 On-Site Disposal

- 1.0 General
- 1.1 Scope

Index

Print Save Email

Contact us

- <u>Privacy policy</u>
 <u>Disclaimer</u>
 <u>Copyright</u>



Feedback