

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print [Save](#) Email

[Resource detail](#)  
[Citations](#)

[View on Information Provider website](#) Download this resource (PDF, 561KB) `{{ linkText }}`

Valid from  
01/07/2001

Format  
PDF

Cites

**This resource cites 1 document (show Citations)**

[View on Information Provider website](#) [Download this resource \(PDF, 561KB\)](#) {{ linkText }}

**For assistance with locating previous versions, please contact the information provider.**

## Verification Method G8/VM1: Artificial Light

Back

## Verification Method G8/VM1: Artificial Light

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Verification Method G8/VM1 provides a means of measuring illuminance for compliance with Building Code Clause G8 Artificial Light.

This clause requires buildings to have sufficient artificial light to safeguard people from injury. It requires spaces within buildings used by people to be provided with adequate artificial lighting to allow safe movement.

It requires illuminance of no less than 20 lux at floor level in exitways, access routes and common spaces within buildings. (Clause F6 Visibility in escape routes applies in the event of main lighting failure).

[View on Information Provider website](#) [Download this resource \(PDF, 561KB\)](#)

### [Verification Method G8/VM1: Artificial Light](#)

This resource is no longer current. The current version is [G8/VM1 \(First Edition, Amendment 2\)](#)

### Description

Verification Method G8/VM1 provides a means of measuring illuminance for compliance with Building Code Clause G8 Artificial Light.

This clause requires buildings to have sufficient artificial light to safeguard people from injury. It requires spaces within buildings used by people to be provided with adequate artificial lighting to allow safe movement.

It requires illuminance of no less than 20 lux at floor level in exitways, access routes and common spaces within buildings. (Clause F6 Visibility in escape routes applies in the event of main lighting failure).

[View on Information Provider website](#) [Download this resource \(PDF, 561KB\)](#)

### This resource cites:

## Verification Method G8/VM1: Artificial Light

### This document CITES:

#### New Zealand Standards

- [NZS 6703:1984](#)

G8/VM1 cites NZS 6703:1984 Code of practice for interior lighting design from 01/07/1992

Back

Close

### Table of Contents

Print

[Save](#)

Email

### [Feedback](#)

- [Contact us](#)

- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)