

Menu

- [Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

Solitex Extasana Wall Underlay

[View on Information Provider website](#) [Download this resource \(PDF, 397KB\)](#)

{{ linkText }}

Abbreviation

GM-CM30032

Version

Rev E - 12 October 2018

Valid from

11/10/2012

Information provider

Ministry of Business, Innovation and Employment

Author

Global-Mark Pty Ltd

Information type

Product Certificate (CodeMark)

Format

PDF

Description

Solitex Extasana Wall Underlay is a flexible synthetic wall underlay for use under direct fixed and non-direct fixed wall cladding on timber and steel framed buildings.

The product consists of a non-porous water resistant film laminated between two layers of non woven spun-bonded polypropylene and is coloured blue on the top surface and grey on the bottom surface.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 397KB\)](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Solitex Extasana Wall Underlay

This document is not CITED BY any other resources:

Back

Solitex Extasana Wall Underlay

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Solitex Extasana Wall Underlay is a flexible synthetic wall underlay for use under direct fixed and non-direct fixed wall cladding on timber and steel framed buildings.

The product consists of a non-porous water resistant film laminated between two layers of non woven spun-bonded polypropylene and is coloured blue on the top surface and grey on the bottom surface.

[View on Information Provider website](#) [Download this resource \(PDF, 397KB\)](#)

[Solitex Extasana Wall Underlay](#)

Description

Solitex Extasana Wall Underlay is a flexible synthetic wall underlay for use under direct fixed and non-direct fixed wall cladding on timber and steel framed buildings.

The product consists of a non-porous water resistant film laminated between two layers of non woven spun-bonded polypropylene and is coloured blue on the top surface and grey on the bottom surface.

[View on Information Provider website](#) [Download this resource \(PDF, 397KB\)](#)

This resource does not cite any other resources.

Solitex Extasana Wall Underlay

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)