

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print [Save](#) Email

[Resource detail](#)

[Citations](#)

## Viking Enviroclad Roofing and Deck Membrane System

[View on Information Provider website](#) [Download this resource \(PDF, 357KB\)](#) {{ linkText }}

### Abbreviation

GM-CM30058

### Version

Revision D, 06/08/2018

### Valid from

28/03/2018

---

### Information provider

Ministry of Business, Innovation and Employment

### Author

Global-Mark Pty Ltd

### Information type

Product Certificate (CodeMark)

### Format

PDF

---

### Description

Viking Enviroclad Roofing and Deck Membrane System is a single ply, polyester fabric reinforced, thermoplastic polyolefin (TPO) waterproofing sheet membrane for flat or pitched roofs and decks.

It can be applied as a fully bonded or mechanically fixed system. Some Membranes are supplied with an APEEL™ protective film.

The film which provides protection during construction is to be removed within 90 days of installation.

### Scope

The main membrane components are:

- STP100 Enviroclad TPO white 1.14mm x 3.0m x 30.4m
- STP500 Enviroclad TPO white 1.52mm x 3.0m x 30.4m
- STP110 Enviroclad TPO grey 1.14mm x 3.0m x 30.4m
- STP110A Enviroclad Apeel TPO grey 1.14mm x 3.0m x 30.4m
- STP510 Enviroclad TPO grey 1.52mm x 3.0m x 30.4m
- STP510A Enviroclad Apeel TPO grey 1.52mm x 3.0m x 30.4m
- STP113 Enviroclad TPO grey 1.14mm x 3.66m wide
- STP513 Enviroclad TPO grey 1.52mm x 3.66m wide
- STP000 Enviroclad adhesive 19L

Viking Enviroclad Roofing and Deck Membrane System must be installed using Viking Roofspec ancillary components as described in the Viking Roofspec Applicator Handbook V1.3 (30/05/2016) referenced as the Handbook.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 357KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

## Viking Enviroclad Roofing and Deck Membrane System

This document is not CITED BY any other resources:

## Viking Enviroclad Roofing and Deck Membrane System

### Description

Viking Enviroclad Roofing and Deck Membrane System is a single ply, polyester fabric reinforced, thermoplastic polyolefin (TPO) waterproofing sheet membrane for flat or pitched roofs and decks.

It can be applied as a fully bonded or mechanically fixed system. Some Membranes are supplied with an APEEL™ protective film.

The film which provides protection during construction is to be removed within 90 days of installation.

[View on Information Provider website](#) [Download this resource \(PDF, 357KB\)](#)

### [Viking Enviroclad Roofing and Deck Membrane System](#)

### Description

Viking Enviroclad Roofing and Deck Membrane System is a single ply, polyester fabric reinforced, thermoplastic polyolefin (TPO) waterproofing sheet membrane for flat or pitched roofs and decks.

It can be applied as a fully bonded or mechanically fixed system. Some Membranes are supplied with an APEEL™ protective film.

The film which provides protection during construction is to be removed within 90 days of installation.

[View on Information Provider website](#) [Download this resource \(PDF, 357KB\)](#)

This resource does not cite any other resources.

## Viking Enviroclad Roofing and Deck Membrane System

This resource does not CITE any other resources.

### Table of Contents

[Save](#)

[Feedback](#)

--	--	--

--

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)