

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

Jet Stream® MAX and Supafil Cavity Insulation - SUSPENDED

[View on Information Provider website](#)

Abbreviation
GM-CM30067-RevB
Version
RevB - 18/07/2019
Valid from
19/07/2016

Information provider
Ministry of Business, Innovation and Employment
Author
Global-Mark Pty Ltd
Information type
Product Certificate (CodeMark)
Format
PDF

Description

Jet Stream MAX and Supafil Cavity Insulation Systems are non-bonded, granulated glasswool fibre materials blown on-site in loose form to a nominal density of 25-28 kg/m³

Scope

Jet Stream MAX and Supafil Cavity Insulation Systems have been assessed for use as a thermal insulation material for new buildings within the following scope:

- Walls when installed in the cavities between framing members;
- Floors when installed in the cavities between flooring members;
- Skillion roofs when installed in the cavities between roofing members.

For assistance with locating previous versions, please contact the information provider.

Notes/comments

This certificate has been suspended by Global-Mark under section 271 of the Building Act 2004 as at 11 June 2020.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This certificate has been suspended by Global-Mark under section 271 of the Building Act 2004 as at 11 June 2020.

This resource is not cited by any other resources.

Jet Stream® MAX and Supafil Cavity Insulation - SUSPENDED

This document is not CITED BY any other resources:

Back

Jet Stream® MAX and Supafil Cavity Insulation - SUSPENDED

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Jet Stream MAX and Supafil Cavity Insulation Systems are non-bonded, granulated glasswool fibre materials blown on-site in loose form to a nominal density of 25-28 kg/m³

[View on Information Provider website](#)

[Jet Stream® MAX and Supafil Cavity Insulation - SUSPENDED](#)

Description

Jet Stream MAX and Supafil Cavity Insulation Systems are non-bonded, granulated glasswool fibre materials blown on-site in loose form to a nominal density of 25-28 kg/m³

[View on Information Provider website](#)

This resource does not cite any other resources.

Jet Stream® MAX and Supafil Cavity Insulation - SUSPENDED

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)