

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

Allied Superslab Concrete Floors

[View on Information Provider website](#) [Download this resource \(PDF, 276KB\)](#)

Abbreviation

GM-CM30086

Version

RevD - 21 June 2019

Valid from

05/07/2017

Information provider

Ministry of Business, Innovation and Employment

Author

Global-Mark Pty Ltd

Information type

Product Certificate (CodeMark)

Format

PDF

Description

Allied Superslab Concrete Floors are waffle pod, reinforced concrete, slab-on-ground floors.

They have been assessed for use for buildings within the following scope:

- Timber framed buildings, up to two storeys high, within the scope of NZS 3604:2011; and
- With a maximum height of 10 m measured from the ground to the apex; and,
- Supported on “good ground” as defined by the Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B1 Ministry of Business, Innovation and Employment, First Edition, July 2005 (Amendment 15, 01 January 2017),
- With a maximum plan floor area of 300 m² and a maximum length of 30 m; and,
- Situated in Wind Zones up to and including Extra High.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 276KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Allied Superslab Concrete Floors

This document is not CITED BY any other resources:

Back

Allied Superslab Concrete Floors

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Allied Superslab Concrete Floors are waffle pod, reinforced concrete, slab-on-ground floors.

They have been assessed for use for buildings within the following scope:

- Timber framed buildings, up to two storeys high, within the scope of NZS 3604:2011; and
- With a maximum height of 10 m measured from the ground to the apex; and,
- Supported on “good ground” as defined by the Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B1 Ministry of Business, Innovation and Employment, First Edition, July 2005 (Amendment 15, 01 January 2017),
- With a maximum plan floor area of 300 m² and a maximum length of 30 m; and,
- Situated in Wind Zones up to and including Extra High.

[View on Information Provider website](#) [Download this resource \(PDF, 276KB\)](#)

[Allied Superslab Concrete Floors](#)

Description

Allied Superslab Concrete Floors are waffle pod, reinforced concrete, slab-on-ground floors.

They have been assessed for use for buildings within the following scope:

- Timber framed buildings, up to two storeys high, within the scope of NZS 3604:2011; and
- With a maximum height of 10 m measured from the ground to the apex; and,
- Supported on “good ground” as defined by the Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B1 Ministry of Business, Innovation and Employment, First Edition, July 2005 (Amendment 15, 01 January 2017),
- With a maximum plan floor area of 300 m² and a maximum length of 30 m; and,
- Situated in Wind Zones up to and including Extra High.

[View on Information Provider website](#) [Download this resource \(PDF, 276KB\)](#)

This resource does not cite any other resources.

Allied Superslab Concrete Floors

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)

- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)