Skip to main content Skip to primary navigation
Menu
Home Home
About this portal
Latest updates
Print Save Email
Resource detail
Citations

# Earthwool® Glasswool Insulation

View on Information Provider website Download this resource (PDF, 349KB) {{ linkText }}

Abbreviation

GM-CM30095

Version

Revision A

Valid from

06/09/2018

Information provider

Ministry of Business, Innovation and Employment

Author

Global Mark Pty Ltd

Information type

Product Certificate (CodeMark)

**Format** 

**PDF** 

### Description

Earthwool® is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as batts or rolls with thickness between 50mm and 275mm, and nominal density between 8 kg/m3 and 30 kg/m3 with binder content no greater than 8%.

Earthwool® is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are:

Earthwool® Acoustic Batts – Basic at 11kg/m3; Ultra at 14 kg/m3; and High-Density at 17 kg/m3, 20 kg/m3 and 27 kg/m3

- Earthwool® Acoustic Roll Basic at 11 kg/m3, High-Density at 24kg/m3
- Earthwool® Ceiling Batts
- Earthwool® Multi-Use Rolls
- Earthwool® Roof Blanket has optional foil backing
- Earthwool® Underfloor Roll faced with a black glass wind wash barrier
- Earthwool® Wall Batts

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website Download this resource (PDF, 349KB)</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

# Earthwool® Glasswool Insulation

This document is not CITED BY any other resources:

Back

# Earthwool® Glasswool Insulation

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Earthwool® is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as batts or rolls with thickness between 50mm and 275mm, and nominal density between 8 kg/m3 and 30 kg/m3 with binder content no greater than 8%.

Earthwool® is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are:

- Earthwool® Acoustic Batts Basic at 11kg/m3; Ultra at 14 kg/m3; and High-Density at 17 kg/m3, 20 kg/m3 and 27 kg/m3
- Earthwool® Acoustic Roll Basic at 11 kg/m3, High-Density at 24kg/m3
- Earthwool® Ceiling Batts
- Earthwool® Multi-Use Rolls
- Earthwool® Roof Blanket has optional foil backing
- Earthwool® Underfloor Roll faced with a black glass wind wash barrier
- Earthwool® Wall Batts

View on Information Provider website Download this resource (PDF, 349KB)

### **Earthwool® Glasswool Insulation**

#### Description

Earthwool® is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as batts or rolls with thickness between 50mm and 275mm, and nominal density between 8 kg/m3 and 30 kg/m3 with binder content no greater than 8%.

Earthwool® is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are:

- Earthwool® Acoustic Batts Basic at 11kg/m3; Ultra at 14 kg/m3; and High-Density at 17 kg/m3, 20 kg/m3 and 27 kg/m3
- Earthwool® Acoustic Roll Basic at 11 kg/m3, High-Density at 24kg/m3
- Earthwool® Ceiling Batts
- Earthwool® Multi-Use Rolls
- Earthwool® Roof Blanket has optional foil backing
- Earthwool® Underfloor Roll faced with a black glass wind wash barrier
- Earthwool® Wall Batts

View on Information Provider website Download this resource (PDF, 349KB)

This resource does not cite any other resources.

# Earthwool® Glasswool Insulation



#### **Table of Contents**

Print Save	Email		
<u>Feedback</u>			

- Contact us
- Privacy policy
- <u>Disclaimer</u>
- Copyright

	_		_

<u>Feedback</u>