

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

Ecoinsulation Glasswool

[View on Information Provider website](#) [Download this resource \(PDF, 281KB\)](#)

Abbreviation
GM-CM30101
Version
Rev A
Valid from
21/02/2019

Information provider
Ministry of Business, Innovation and Employment
Information type
Product Certificate (CodeMark)
Format
PDF

Description

Ecoinsulation Glasswool is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as segments or rolls with thickness between 70 mm and 275 mm, and nominal density between 7.7 kg/m³ and 29.1kg/m³ with binder content no greater than 8%.

Ecoinsulation Glasswool is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are listed below:

- Ecoinsulation – Ceiling Batts
- Ecoinsulation – Ceiling Rolls
- Ecoinsulation – Quilted Underfloor Batts
- Ecoinsulation – Black Faced Underfloor Rolls
- Ecoinsulation – Wall Batts

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 281KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Ecoinsulation Glasswool

This document is not CITED BY any other resources:

Back

Ecoinsulation Glasswool

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Ecoinsulation Glasswool is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as segments or rolls with thickness between 70 mm and 275 mm, and nominal density between 7.7 kg/m³ and 29.1kg/m³ with binder content no greater than 8%.

Ecoinsulation Glasswool is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are listed below:

- Ecoinsulation – Ceiling Batts
- Ecoinsulation – Ceiling Rolls
- Ecoinsulation – Quilted Underfloor Batts
- Ecoinsulation – Black Faced Underfloor Rolls
- Ecoinsulation – Wall Batts

[View on Information Provider website](#) [Download this resource \(PDF, 281KB\)](#)

[Ecoinsulation Glasswool](#)

Description

Ecoinsulation Glasswool is a mineral fibre type bulk insulation that complies with AS/NZS 4859.1:2002 (incorporating Amendment No.1) and is supplied as segments or rolls with thickness between 70 mm and 275 mm, and nominal density between 7.7 kg/m³ and 29.1kg/m³ with binder content no greater than 8%.

Ecoinsulation Glasswool is manufactured with recycled glass and ECOSE® Technology binder which is created from renewable materials. The product types and special characteristics are listed below:

- Ecoinsulation – Ceiling Batts
- Ecoinsulation – Ceiling Rolls
- Ecoinsulation – Quilted Underfloor Batts
- Ecoinsulation – Black Faced Underfloor Rolls
- Ecoinsulation – Wall Batts

[View on Information Provider website](#) [Download this resource \(PDF, 281KB\)](#)

This resource does not cite any other resources.

Ecoinsulation Glasswool

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)