

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## IEC 60309-1:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements

[View on Information Provider website](#)

### Abbreviation

IEC 60309-1:1999

### Valid from

26/02/1999

---

### Information provider

International Electrotechnical Commission

### Author

International Electrotechnical Commission

### Information type

IEC Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

Applies to plugs and socket-outlets, cable couplers and appliance couplers, with a rated operating voltage not exceeding 690 V d.c. or a.c., 500 Hz a.c. and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors when the ambient temperature does not normally exceed 40°C.

This publication is of high relevance for Smart Grid.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## IEC 60309-1:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements

This document is CITED BY:

- [AS/NZS 3000:2007](#)

IEC 60309-1:1999 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

Back

## IEC 60309-1:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Applies to plugs and socket-outlets, cable couplers and appliance couplers, with a rated operating voltage not exceeding 690 V d.c. or a.c., 500 Hz a.c. and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors when the ambient temperature does not normally exceed 40°C.

This publication is of high relevance for Smart Grid.

[View on Information Provider website](#)

[IEC 60309-1:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements](#)

### Description

Applies to plugs and socket-outlets, cable couplers and appliance couplers, with a rated operating voltage not exceeding 690 V d.c. or a.c., 500 Hz a.c. and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors when the ambient temperature does not normally exceed 40°C.

This publication is of high relevance for Smart Grid.

[View on Information Provider website](#)

This resource does not cite any other resources.

## IEC 60309-1:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

  
  

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)