

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  
 

[Save](#)

[Resource detail](#)  
[Citations](#)

## IEC 60309-2:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories

[View on Information Provider website](#)

### Abbreviation

IEC 60309-2:1999

### Valid from

12/04/1999

---

### Information provider

International Electrotechnical Commission

### Author

International Electrotechnical Commission

### Information type

IEC Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

Applies to plugs and socket-outlets, cable couplers with a rated operating voltage not exceeding 690 V, 500 Hz and a rated current not exceeding 125 A, primarily intended for industrial use, either indoors or outdoors.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## IEC 60309-2:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories

This document is CITED BY:

- [AS/NZS 3000:2007](#)

IEC 60309-2:1999 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

Back

## IEC 60309-2:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Applies to plugs and socket-outlets, cable couplers with a rated operating voltage not exceeding 690 V, 500 Hz and a rated current not exceeding 125 A, primarily intended for industrial use, either indoors or outdoors.

[View on Information Provider website](#)

[IEC 60309-2:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories](#)

### Description

Applies to plugs and socket-outlets, cable couplers with a rated operating voltage not exceeding 690 V, 500 Hz and a rated current not exceeding 125 A, primarily intended for industrial use, either indoors or outdoors.

[View on Information Provider website](#)

This resource does not cite any other resources.

## IEC 60309-2:1999 Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

  
  

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

