Skip to main content Skip to primary navigation
Menu
Home Home
About this portal
Latest updates
Print Save Email
Resource detail Citations
<u>Citations</u>
IEC 60309-4:2006 Plugs, socket-outlets and couplers for industrial purposes -
• •
Part 4: Switched socket-outlets and connectors with or without interlock
View on Information Provider website {{ linkText }}
Abbreviation
IEC 60309-4:2006
Valid from
22/06/2006
Information provider
International Electrotechnical Commission
Author
International Electrotechnical Commission
Information type
IEC Standard
Format
PDF
Cited By
This resource is cited by 1 document (show Citations)
This resource is thea by a document (show ortations)
Description
This part of IEC 60309 applies to self-contained products that combine within a single enclosure, a socket-outlet or connector
according to IEC 60309-1 or IEC 60309-2 and a switching device, with a rated operating voltage not exceeding 690 V d.c. or a.c
and 500 Hz, and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors.
For accistance with locating provious versions, please contact the information provider
For assistance with locating previous versions, please contact the information provider.
ACTION OF THE PROPERTY AND ACTION OF THE PROPERT
View on Information Provider website {{ linkText }}
For assistance with locating previous versions, please contact the information provider.

IEC 60309-4:2006 Plugs, socket-outlets and couplers for industrial purposes - Part 4: Switched socket-outlets and connectors with or without interlock

This document is CITED BY:

This resource is cited by:

AS/NZS 3000:2007

IEC 60309-4:2006 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

Back

## IEC 60309-4:2006 Plugs, socket-outlets and couplers for industrial purposes - Part 4: Switched socket-outlets and connectors with or without interlock

Show what documents this resource is CITED BY Show what do

Show what documents this resource CITES

Description

This part of IEC 60309 applies to self-contained products that combine within a single enclosure, a socket-outlet or connector according to IEC 60309-1 or IEC 60309-2 and a switching device, with a rated operating voltage not exceeding 690 V d.c. or a.c. and 500 Hz, and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors.

View on Information Provider website

IEC 60309-4:2006 Plugs, socket-outlets and couplers for industrial purposes - Part 4: Switched socket-outlets and connectors with or without interlock

Description

This part of IEC 60309 applies to self-contained products that combine within a single enclosure, a socket-outlet or connector according to IEC 60309-1 or IEC 60309-2 and a switching device, with a rated operating voltage not exceeding 690 V d.c. or a.c. and 500 Hz, and a rated current not exceeding 250 A, primarily intended for industrial use, either indoors or outdoors.

View on Information Provider website

This resource does not cite any other resources.

## IEC 60309-4:2006 Plugs, socket-outlets and couplers for industrial purposes - Part 4: Switched socket-outlets and connectors with or without interlock

This resource does not CITE any other resources.	
Back	
Table of Contents	
Print Save Email Feedback	
<ul> <li>Contact us</li> <li>Privacy policy</li> <li>Disclaimer</li> <li>Copyright</li> </ul>	
Feedback	