

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)  
[Citations](#)

## IEC 60439-1:1999 Low-voltage switchgear and controlgear assemblies - Part 1: Type-tested and partially type-tested assemblies

[View on Information Provider website](#)

### Abbreviation

IEC 60439-1:1999

### Valid from

30/09/1999

---

### Information provider

International Electrotechnical Commission

### Author

International Electrotechnical Commission

### Information type

IEC Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This standard applies to low-voltage switchgear and controlgear assemblies (type-tested assemblies (TTA) and partially type-tested assemblies (PTTA)), the rated voltage of which does not exceed 1000 V a.c. at frequencies not exceeding 1000 Hz, or 1500 V d.c.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## IEC 60439-1:1999 Low-voltage switchgear and controlgear assemblies - Part 1: Type-tested and partially type-tested assemblies

This document is CITED BY:

- [BS EN 115-1:2008](#)

Back

## IEC 60439-1:1999 Low-voltage switchgear and controlgear assemblies - Part 1: Type-tested and partially type-tested assemblies

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This standard applies to low-voltage switchgear and controlgear assemblies (type-tested assemblies (TTA) and partially type-tested assemblies (PTTA)), the rated voltage of which does not exceed 1000 V a.c. at frequencies not exceeding 1000 Hz, or 1500 V d.c.

[View on Information Provider website](#)

[IEC 60439-1:1999 Low-voltage switchgear and controlgear assemblies - Part 1: Type-tested and partially type-tested assemblies](#)

### Description

This standard applies to low-voltage switchgear and controlgear assemblies (type-tested assemblies (TTA) and partially type-tested assemblies (PTTA)), the rated voltage of which does not exceed 1000 V a.c. at frequencies not exceeding 1000 Hz, or 1500 V d.c.

[View on Information Provider website](#)

This resource does not cite any other resources.

## IEC 60439-1:1999 Low-voltage switchgear and controlgear assemblies - Part 1: Type-tested and partially type-tested assemblies

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)