

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

IEC 60584-2:1982+AMD1:1989 (Consolidated version) Thermocouples. Part 2: Tolerances

[View on Information Provider website](#)

Abbreviation

IEC 60584-2:1982+AMD1:1989

Amendment

AMD1:1989

Valid from

01/01/1982

Information provider

International Electrotechnical Commission

Author

International Electrotechnical Commission

Information type

IEC Standard

Format

PDF

Cited By

[This resource is cited by 3 documents \(show Citations\)](#)

Description

Contains the manufacturing tolerances for both noble and base metal thermocouples manufactured in accordance with e.m.f. temperature relationships of Part 1 of the standard.

The tolerance values are for a thermocouple manufactured from wires normally in the diameter range 0.25 mm to 3 mm, as delivered to the user and do not allow for calibration draft during use.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 60584-2:1982+AMD1:1989 (Consolidated version) Thermocouples. Part 2: Tolerances

This document is CITED BY:

- [ISO 1182:2010](#)

IEC 60584-2:1982+AMD1:1989 is cited by ISO 1182:2010 Reaction to fire tests for products - Non-combustibility test

- [ISO 13784:1:2002](#)

IEC 60584-2:1982+AMD1:1989 is cited by ISO 13784-1:2002 Reaction-to-fire tests for sandwich panel building systems - Test method for small rooms

- [ISO 13785-1:2002](#)

IEC 60584-2:1982+AMD1:1989 is cited by ISO 13785-1:2002 Reaction-to-fire tests for facades - Intermediate-scale test

Back

IEC 60584-2:1982+AMD1:1989 (Consolidated version) Thermocouples. Part 2: Tolerances

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Contains the manufacturing tolerances for both noble and base metal thermocouples manufactured in accordance with e.m.f. temperature relationships of Part 1 of the standard.

The tolerance values are for a thermocouple manufactured from wires normally in the diameter range 0.25 mm to 3 mm, as delivered to the user and do not allow for calibration draft during use.

[View on Information Provider website](#)

[IEC 60584-2:1982+AMD1:1989 \(Consolidated version\) Thermocouples. Part 2: Tolerances](#)

Description

Contains the manufacturing tolerances for both noble and base metal thermocouples manufactured in accordance with e.m.f. temperature relationships of Part 1 of the standard.

The tolerance values are for a thermocouple manufactured from wires normally in the diameter range 0.25 mm to 3 mm, as delivered to the user and do not allow for calibration draft during use.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 60584-2:1982+AMD1:1989 (Consolidated version) Thermocouples. Part 2: Tolerances

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

--	--	--

--

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)