

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

IEC 61249-2-10:2003 Materials for printed boards and other interconnecting structures - Part 2-10: Reinforced base materials clad and unclad - Cyanate ester, brominated epoxide, modified or unmodified, woven E-glass reinforced laminated sheets of define

[View on Information Provider website](#)

Abbreviation

IEC 61249-2-10:2003

Valid from

27/02/2003

Information provider

International Organisation for Standardization

Author

International Organisation for Standardization

Information type

IEC Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of cyanate ester, brominated epoxide modified or unmodified woven E-glass laminate sheets of defined flammability, copper-clad, in thicknesses of 0,05 mm to 3,2 mm. The flammability rating is achieved through the use of brominated fire retardants contained as an integral part of the epoxide polymeric structure.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-10:2003 Materials for printed boards and other interconnecting structures - Part 2-10: Reinforced base materials clad and unclad - Cyanate ester, brominated epoxide, modified or unmodified, woven E-glass reinforced

laminated sheets of define

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-10:2003 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-10:2003 Materials for printed boards and other interconnecting structures - Part 2-10: Reinforced base materials clad and unclad - Cyanate ester, brominated epoxide, modified or unmodified, woven E-glass reinforced laminated sheets of define

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of cyanate ester, brominated epoxide modified or unmodified woven E-glass laminate sheets of defined flammability, copper-clad, in thicknesses of 0,05 mm to 3,2 mm. The flammability rating is achieved through the use of brominated fire retardants contained as an integral part of the epoxide polymeric structure.

[View on Information Provider website](#)

[IEC 61249-2-10:2003 Materials for printed boards and other interconnecting structures - Part 2-10: Reinforced base materials clad and unclad - Cyanate ester, brominated epoxide, modified or unmodified, woven E-glass reinforced laminated sheets of define](#)

Description

This part of IEC 61249 gives requirements for properties of cyanate ester, brominated epoxide modified or unmodified woven E-glass laminate sheets of defined flammability, copper-clad, in thicknesses of 0,05 mm to 3,2 mm. The flammability rating is achieved through the use of brominated fire retardants contained as an integral part of the epoxide polymeric structure.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-10:2003 Materials for printed boards and other interconnecting structures - Part 2-10: Reinforced base materials clad and unclad - Cyanate ester, brominated epoxide, modified or unmodified, woven E-glass reinforced laminated sheets of define

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)