

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)

[Citations](#)

## IEC 61249-2-12:1999 Materials for printed boards and other interconnecting structures - Part 2-12: Sectional specification set for reinforced base materials, clad and unclad - Epoxide non-woven aramid laminate of defined flammability, copper-clad

[View on Information Provider website](#)

Abbreviation

IEC 61249-2-12:1999

Valid from

29/01/1999

---

Information provider

International Organisation for Standardization

Author

International Organisation for Standardization

Information type

IEC Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

Description

This part of IEC 61249 gives requirements for properties of epoxide non-woven aramid copper clad laminate of defined flammability, in thicknesses of 0,05 mm up to 6,4 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

**IEC 61249-2-12:1999 Materials for printed boards and other interconnecting structures - Part 2-12: Sectional specification set for reinforced base materials, clad and unclad - Epoxide non-woven aramid laminate of defined flammability,**

# copper-clad

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-12:1999 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

## IEC 61249-2-12:1999 Materials for printed boards and other interconnecting structures - Part 2-12: Sectional specification set for reinforced base materials, clad and unclad - Epoxide non-woven aramid laminate of defined flammability, copper-clad

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This part of IEC 61249 gives requirements for properties of epoxide non-woven aramid copper clad laminate of defined flammability, in thicknesses of 0,05 mm up to 6,4 mm.

[View on Information Provider website](#)

[IEC 61249-2-12:1999 Materials for printed boards and other interconnecting structures - Part 2-12: Sectional specification set for reinforced base materials, clad and unclad - Epoxide non-woven aramid laminate of defined flammability, copper-clad](#)

### Description

This part of IEC 61249 gives requirements for properties of epoxide non-woven aramid copper clad laminate of defined flammability, in thicknesses of 0,05 mm up to 6,4 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

## IEC 61249-2-12:1999 Materials for printed boards and other interconnecting structures - Part 2-12: Sectional specification set for reinforced base materials, clad and unclad - Epoxide non-woven aramid laminate of defined flammability, copper-clad

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)