

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

Save

Email

[Resource detail](#)  
[Citations](#)

# IEC 61249-2-18:2002 Materials for printed boards and other interconnecting structures - Part 2-18: Reinforced base materials, clad and unclad - Polyester non-woven fibreglass reinforced laminated sheet of defined flammability (vertical burning test), co

[View on Information Provider website](#)

{{ linkText }}

Abbreviation  
IEC 61249-2-18:2002  
Valid from  
13/02/2002

Information provider  
International Electrotechnical Commission  
Author  
International Electrotechnical Commission  
Information type  
IEC Standard  
Format  
PDF

Cited By  
[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of polyester non-woven E-glass reinforced copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# IEC 61249-2-18:2002 Materials for printed boards and other interconnecting structures - Part 2-18: Reinforced base materials, clad and unclad - Polyester non-woven fibreglass reinforced laminated sheet of defined flammability

## (vertical burning test), co

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-18:2002 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

## IEC 61249-2-18:2002 Materials for printed boards and other interconnecting structures - Part 2-18: Reinforced base materials, clad and unclad - Polyester non-woven fibreglass reinforced laminated sheet of defined flammability (vertical burning test), co

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This part of IEC 61249 gives requirements for properties of polyester non-woven E-glass reinforced copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

[View on Information Provider website](#)

[IEC 61249-2-18:2002 Materials for printed boards and other interconnecting structures - Part 2-18: Reinforced base materials, clad and unclad - Polyester non-woven fibreglass reinforced laminated sheet of defined flammability \(vertical burning test\), co](#)

### Description

This part of IEC 61249 gives requirements for properties of polyester non-woven E-glass reinforced copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

## IEC 61249-2-18:2002 Materials for printed boards and other interconnecting structures - Part 2-18: Reinforced base materials, clad and unclad - Polyester non-woven fibreglass reinforced laminated sheet of defined flammability (vertical burning test), co

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)