

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

IEC 61249-2-19:2001 Materials for printed boards and other interconnecting structures - Part 2-19: Reinforced base materials, clad and unclad - Epoxide cross-plyed linear fibreglass-reinforced laminated sheets of defined flammability (vertical burning tes

[View on Information Provider website](#)

Abbreviation
IEC 61249-2-19:2001
Valid from
28/11/2001

Information provider
International Electrotechnical Commission
Author
International Electrotechnical Commission
Information type
IEC Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of epoxide linear fibreglass reinforced copper-clad laminated sheet, of defined flammability, with a tickness range from 0,05 mm to 0,40 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-19:2001 Materials for printed boards and other interconnecting structures - Part 2-19: Reinforced base materials, clad and unclad - Epoxide cross-plyed linear fibreglass-reinforced laminated sheets of defined

flammability (vertical burning tes

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-19:2001 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-19:2001 Materials for printed boards and other interconnecting structures - Part 2-19: Reinforced base materials, clad and unclad - Epoxide cross-plyed linear fibreglass-reinforced laminated sheets of defined flammability (vertical burning tes

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of epoxide linear fibreglass reinforced copper-clad laminated sheet, of defined flammability, with a tickness range from 0,05 mm to 0,40 mm.

[View on Information Provider website](#)

[IEC 61249-2-19:2001 Materials for printed boards and other interconnecting structures - Part 2-19: Reinforced base materials, clad and unclad - Epoxide cross-plyed linear fibreglass-reinforced laminated sheets of defined flammability \(vertical burning tes](#)

Description

This part of IEC 61249 gives requirements for properties of epoxide linear fibreglass reinforced copper-clad laminated sheet, of defined flammability, with a tickness range from 0,05 mm to 0,40 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-19:2001 Materials for printed boards and other interconnecting structures - Part 2-19: Reinforced base materials, clad and unclad - Epoxide cross-plyed linear fibreglass-reinforced laminated sheets of defined flammability (vertical burning tes

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)