

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)
[Citations](#)

IEC 61249-2-21:2003 Materials for printed boards and other interconnecting structures - Part 2-21: Reinforced base materials, clad and unclad - Non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability (vertical burning tes

[View on Information Provider website](#)

{{ linkText }}

Abbreviation
 IEC 61249-2-21:2003
 Valid from
 12/11/2003

Information provider
 International Electrotechnical Commission
 Author
 International Electrotechnical Commission
 Information type
 IEC Standard
 Format
 PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability, copper-clad in thicknesses 0,05 mm up to 3,2 mm. The flammability rating is achieved through the use of non-halogenated inorganic and/or organic compounds acting as fire retardants.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-21:2003 Materials for printed boards and other interconnecting structures - Part 2-21: Reinforced base materials, clad and unclad - Non-halogenated epoxide woven E-glass reinforced laminated sheets of defined

flammability (vertical burning tes

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-21:2003 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-21:2003 Materials for printed boards and other interconnecting structures - Part 2-21: Reinforced base materials, clad and unclad - Non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability (vertical burning tes

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability, copper-clad in thicknesses 0,05 mm up to 3,2 mm. The flammability rating is achieved through the use of non-halogenated inorganic and/or organic compounds acting as fire retardants.

[View on Information Provider website](#)

[IEC 61249-2-21:2003 Materials for printed boards and other interconnecting structures - Part 2-21: Reinforced base materials, clad and unclad - Non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability \(vertical burning tes](#)

Description

This part of IEC 61249 gives requirements for properties of non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability, copper-clad in thicknesses 0,05 mm up to 3,2 mm. The flammability rating is achieved through the use of non-halogenated inorganic and/or organic compounds acting as fire retardants.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-21:2003 Materials for printed boards and other interconnecting structures - Part 2-21: Reinforced base materials, clad and unclad - Non-halogenated epoxide woven E-glass reinforced laminated sheets of defined flammability (vertical burning tes

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

--	--	--

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)