

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

IEC 61249-2-4:2001 Materials for printed boards and other interconnecting structures - Part 2-4: Reinforced base materials, clad and unclad - Polyester non-woven/woven fibreglass laminated sheet of defined flammability (vertical burning test), copper-cl

[View on Information Provider website](#)

Abbreviation

IEC 61249-2-4:2001

Version

Edition 1.0

Valid from

19/12/2001

Information provider

International Electrotechnical Commission

Author

International Electrotechnical Commission

Information type

IEC Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of polyester woven fibreglass reinforced surface / non-woven fibreglass reinforced core copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-4:2001 Materials for printed boards and other interconnecting structures - Part 2-4: Reinforced base materials, clad and unclad - Polyester

non-woven/woven fibreglass laminated sheet of defined flammability (vertical burning test), copper-cl

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-4:2001 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-4:2001 Materials for printed boards and other interconnecting structures - Part 2-4: Reinforced base materials, clad and unclad - Polyester non-woven/woven fibreglass laminated sheet of defined flammability (vertical burning test), copper-cl

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of polyester woven fibreglass reinforced surface / non-woven fibreglass reinforced core copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

[View on Information Provider website](#)

[IEC 61249-2-4:2001 Materials for printed boards and other interconnecting structures - Part 2-4: Reinforced base materials, clad and unclad - Polyester non-woven/woven fibreglass laminated sheet of defined flammability \(vertical burning test\), copper-cl](#)

Description

This part of IEC 61249 gives requirements for properties of polyester woven fibreglass reinforced surface / non-woven fibreglass reinforced core copper-clad laminated sheet, of defined flammability, in thicknesses of 0,80 mm to 1,60 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-4:2001 Materials for printed boards and other interconnecting structures - Part 2-4: Reinforced base materials, clad and unclad - Polyester non-woven/woven fibreglass laminated sheet of defined flammability (vertical burning test), copper-cl

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)