

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

IEC 61249-2-6:2003 Materials for printed boards and other interconnecting structures - Part 2-6: Reinforced base materials, clad and unclad - Brominated epoxide non-woven/woven E-glass reinforced laminated sheets of defined flammability, copper-clad

[View on Information Provider website](#)

Abbreviation
IEC 61249-2-6:2003
Valid from
12/11/2003

Information provider
International Electrotechnical Commission
Author
International Electrotechnical Commission
Information type
IEC Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of brominated epoxide non-woven/woven reinforced E-glass laminated sheets of defined flammability, copper-clad in thicknesses of 0,80 mm up to 1,70 mm. The flammability rating is achieved through the use of brominated fire retardants reacted as part of the epoxide polymeric structure.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-6:2003 Materials for printed boards and other interconnecting structures - Part 2-6: Reinforced base materials, clad and unclad - Brominated epoxide non-woven/woven E-glass reinforced laminated sheets of defined

flammability, copper-clad

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-6:2003 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-6:2003 Materials for printed boards and other interconnecting structures - Part 2-6: Reinforced base materials, clad and unclad - Brominated epoxide non-woven/woven E-glass reinforced laminated sheets of defined flammability, copper-clad

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of brominated epoxide non-woven/woven reinforced E-glass laminated sheets of defined flammability, copper-clad in thicknesses of 0,80 mm up to 1,70 mm. The flammability rating is achieved through the use of brominated fire retardants reacted as part of the epoxide polymeric structure.

[View on Information Provider website](#)

[IEC 61249-2-6:2003 Materials for printed boards and other interconnecting structures - Part 2-6: Reinforced base materials, clad and unclad - Brominated epoxide non-woven/woven E-glass reinforced laminated sheets of defined flammability, copper-clad](#)

Description

This part of IEC 61249 gives requirements for properties of brominated epoxide non-woven/woven reinforced E-glass laminated sheets of defined flammability, copper-clad in thicknesses of 0,80 mm up to 1,70 mm. The flammability rating is achieved through the use of brominated fire retardants reacted as part of the epoxide polymeric structure.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-6:2003 Materials for printed boards and other interconnecting structures - Part 2-6: Reinforced base materials, clad and unclad - Brominated epoxide non-woven/woven E-glass reinforced laminated sheets of defined flammability, copper-clad

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)