

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

IEC 61249-2-9:2003 Materials for printed boards and other interconnecting structures - Part 2-9: Reinforced base materials, clad and unclad - Bismaleimide/triazine modified epoxide or unmodified, woven E-glass reinforced laminated sheets of defined flam

[View on Information Provider website](#)

Abbreviation

IEC 61249-2-9:2003

Valid from

27/02/2003

Information provider

International Electrotechnical Commission

Author

International Electrotechnical Commission

Information type

IEC Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of IEC 61249 gives requirements for properties of bismaleimide/triazine modified epoxide, or unmodified, woven E-glass reinforced laminate sheets of defined flammability, copper-clad in thicknesses of 0,05 mm to 3,2 mm.

The flammability rating is achieved through the use of fire retardants contained as an integral part of the epoxide polymeric structure.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

IEC 61249-2-9:2003 Materials for printed boards and other interconnecting

structures - Part 2-9: Reinforced base materials, clad and unclad - Bismaleimide/triazine modified epoxide or unmodified, woven E-glass reinforced laminated sheets of defined flam

This document is CITED BY:

- [BS EN 115-1:2008](#)

IEC 61249-2-9:2003 is cited by BS EN 115-1:2008 Safety of escalators and moving walks Part 1: Construction and installation

Back

IEC 61249-2-9:2003 Materials for printed boards and other interconnecting structures - Part 2-9: Reinforced base materials, clad and unclad - Bismaleimide/triazine modified epoxide or unmodified, woven E-glass reinforced laminated sheets of defined flam

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of IEC 61249 gives requirements for properties of bismaleimide/triazine modified epoxide, or unmodified, woven E-glass reinforced laminate sheets of defined flammability, copper-clad in thicknesses of 0,05 mm to 3,2 mm.

The flammability rating is achieved through the use of fire retardants contained as an integral part of the epoxide polymeric structure.

[View on Information Provider website](#)

[IEC 61249-2-9:2003 Materials for printed boards and other interconnecting structures - Part 2-9: Reinforced base materials, clad and unclad - Bismaleimide/triazine modified epoxide or unmodified, woven E-glass reinforced laminated sheets of defined flam](#)

Description

This part of IEC 61249 gives requirements for properties of bismaleimide/triazine modified epoxide, or unmodified, woven E-glass reinforced laminate sheets of defined flammability, copper-clad in thicknesses of 0,05 mm to 3,2 mm.

The flammability rating is achieved through the use of fire retardants contained as an integral part of the epoxide polymeric structure.

[View on Information Provider website](#)

This resource does not cite any other resources.

IEC 61249-2-9:2003 Materials for printed boards and other interconnecting structures - Part 2-9: Reinforced base materials, clad and unclad - Bismaleimide/triazine modified epoxide or unmodified, woven E-glass reinforced laminated sheets of defined flam

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)