| <u>Skip to main content Skip to primary navigation</u> |
|--|
| Menu   |
| Home Home  |
|  |
| <u>About this portal</u>                               |
| Latest updates   |
|  |
|  |
|  |
| Print Save Email                                       |
|  |
| Resource detail  |
| Citations  |

ISO 13783:1997 Plastics piping systems - Unplasticized poly(vinyl chloride) (PVC-U) end-load-bearing double-socket joints - Test method for leaktightness and strength while subjected to bending and internal pressure

| View on Information Provider website {{ linkText }}                                |
|--|
| Abbreviation<br>ISO 13783:1997   |
| Valid from<br>28/08/1997   |
| Information provider<br>Standards New Zealand<br>Author                            |
| International Organization for Standardization<br>Information type<br>ISO Standard |
| Format<br>PDF  |

Cited By <u>This resource is cited by 1 document (show Citations)</u>

#### Description

This standard specifies a method for testing, while subjected to bending, the leaktightness and strength of assembled end-loadbearing double socket joints of unplasticized poly(vinyl chloride) (PVC-U) which allow a maximum angle of deflection of 3.

It is applicable to double socket couplers provided with elastomeric sealing rings and locking rings and intended for use with PVC-U pressure pipes (see figure 1).

The method specifies the internal pressure, the method of calculation for the additional bending force and the procedure for the bending test.

For assistance with locating previous versions, please contact the information provider.

View on Information Provider website {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

### ISO 13783:1997 Plastics piping systems - Unplasticized poly(vinyl chloride)

# (PVC-U) end-load-bearing double-socket joints - Test method for leaktightness and strength while subjected to bending and internal pressure

This document is CITED BY:

#### • <u>AS/NZS 4765:2007</u>

ISO 13783:1997 is cited by AS/NZS 4765:2007 Modified polyvinyl chloride (PVC-M) pipes for pressure applications

Back

## ISO 13783:1997 Plastics piping systems - Unplasticized poly(vinyl chloride) (PVC-U) end-load-bearing double-socket joints - Test method for leaktightness and strength while subjected to bending and internal pressure

Show what documents this resource is CITED BY Show what documents this resource CITES

#### Description

This standard specifies a method for testing, while subjected to bending, the leaktightness and strength of assembled end-loadbearing double socket joints of unplasticized poly(vinyl chloride) (PVC-U) which allow a maximum angle of deflection of 3.

It is applicable to double socket couplers provided with elastomeric sealing rings and locking rings and intended for use with PVC-U pressure pipes (see figure 1).

The method specifies the internal pressure, the method of calculation for the additional bending force and the procedure for the bending test.

#### View on Information Provider website

ISO 13783:1997 Plastics piping systems - Unplasticized poly(vinyl chloride) (PVC-U) end-load-bearing double-socket joints - Test method for leaktightness and strength while subjected to bending and internal pressure

#### Description

This standard specifies a method for testing, while subjected to bending, the leaktightness and strength of assembled end-loadbearing double socket joints of unplasticized poly(vinyl chloride) (PVC-U) which allow a maximum angle of deflection of 3.

It is applicable to double socket couplers provided with elastomeric sealing rings and locking rings and intended for use with PVC-U pressure pipes (see figure 1).

The method specifies the internal pressure, the method of calculation for the additional bending force and the procedure for the bending test.

#### View on Information Provider website

This resource does not cite any other resources.

## ISO 13783:1997 Plastics piping systems - Unplasticized poly(vinyl chloride) (PVC-U) end-load-bearing double-socket joints - Test method for leaktightness and strength while subjected to bending and internal pressure

This resource does not CITE any other resources.



#### Table of Contents



Feedback