

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ISO 13954:1997 Plastics pipes and fittings - Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm

[View on Information Provider website](#)

Abbreviation
ISO 13954:1997
Valid from
15/12/1997

Information provider
Standards New Zealand
Author
International Organization for Standardization
Information type
ISO Standard
Format
PDF, Hard copy

Cited By
[This resource is cited by 2 documents \(show Citations\)](#)

Description

This International standard describes a peel test method for determining the decohesive resistance of polyethylene electrofusion socket assemblies for use in the distribution of fluids. This method is applicable to assemblies with nominal outside diameters greater than or equal to 90 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 13954:1997 Plastics pipes and fittings - Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm

This document is CITED BY:

- [AS/NZS 4129:2008](#)

ISO 13954:1997 is cited by AS/NZS 4129:2008 Fittings for polyethylene (PE) pipes for pressure applications

- [AS/NZS 5065:2005](#)

ISO 13954:1997 is cited by AS/NZS 5065:2005 (R2016) Polyethylene and polypropylene pipes and fittings for drainage and sewerage applications

Back

ISO 13954:1997 Plastics pipes and fittings - Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This International standard describes a peel test method for determining the decohesive resistance of polyethylene electrofusion socket assemblies for use in the distribution of fluids. This method is applicable to assemblies with nominal outside diameters greater than or equal to 90 mm.

[View on Information Provider website](#)

[ISO 13954:1997 Plastics pipes and fittings - Peel decohesion test for polyethylene \(PE\) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm](#)

Description

This International standard describes a peel test method for determining the decohesive resistance of polyethylene electrofusion socket assemblies for use in the distribution of fluids. This method is applicable to assemblies with nominal outside diameters greater than or equal to 90 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

ISO 13954:1997 Plastics pipes and fittings - Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

