Skip to main content Skip Menu	to primary navigation	
 Home Home About this portal Latest updates		
Print Save Email Resource detail		

ISO 13955:1997 Plastics pipes and fittings - Crushing decohesion test for polyethylene (PE) electrofusion assemblies

<u>View on Information Provider website</u> {{ linkText }}

Abbreviation ISO 13955:1997 Valid from 15/12/1997

Citations

Information provider
Standards New Zealand
Author
International Organization for Standardization
Information type
ISO Standard
Format
PDF, Hard copy

Cited By

This resource is cited by 2 documents (show Citations)

Description

This International Standard describes a crushing test method for determining the decohesive resistance of polyethylene (PE) pipe and electrofusion socket or saddle assemblies for use in the distribution of fluids. The method is applicable to assemblies with pipes of nominal outside diameter between 16 mm and 225 mm.

 $\label{previous previous previous previous previous} For assistance with locating previous versions, please contact the information provider.$

View on Information Provider website {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 13955:1997 Plastics pipes and fittings - Crushing decohesion test for polyethylene (PE) electrofusion assemblies

This document is CITED BY:

• AS/NZS 4129:2008

ISO 13955:1997 is cited by AS/NZS 4129:2008 Fittings for polyethylene (PE) pipes for pressure applications

• AS/NZS 5065:2005

Back

ISO 13955:1997 Plastics pipes and fittings - Crushing decohesion test for polyethylene (PE) electrofusion assemblies

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

This International Standard describes a crushing test method for determining the decohesive resistance of polyethylene (PE) pipe and electrofusion socket or saddle assemblies for use in the distribution of fluids. The method is applicable to assemblies with pipes of nominal outside diameter between 16 mm and 225 mm.

View on Information Provider website

ISO 13955:1997 Plastics pipes and fittings - Crushing decohesion test for polyethylene (PE) electrofusion assemblies

Description

This International Standard describes a crushing test method for determining the decohesive resistance of polyethylene (PE) pipe and electrofusion socket or saddle assemblies for use in the distribution of fluids. The method is applicable to assemblies with pipes of nominal outside diameter between 16 mm and 225 mm.

View on Information Provider website

This resource does not CITE any other resources.

This resource does not cite any other resources.

ISO 13955:1997 Plastics pipes and fittings - Crushing decohesion test for polyethylene (PE) electrofusion assemblies

Table of Contents

Print Save Email
Feedback

Contact us
Privacy policy
Disclaimer
Copyright

Feedback